

Product Search Data Sheet

## CSTCE16M9V53Z-R0


REACH

Discontinued RoHS

Applications

| Unsuitable               | Please be sure to read and comply with     |
|--------------------------|--|
| Applications             | these "Precautions for use."               |
| Specific<br>Applications | Consumer equipment                         |
|                          | Please refer to Our Website and            |
|                          | specifications, etc. for information about |
|                          | the performance, functions, quality,       |
|                          | management, and safety required for        |
|                          | the above applications, and use            |
|                          | Products after confirming the              |
|                          | performance and reliability of the actual  |
|                          | Product.                                   |

## Appearance & Shape



Note: This datasheet may be out of date. Please download the latest datasheet of CSTCE16M9V53Z-R0 from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en-gb/products/productdetail?partno=CSTCE16M9V53Z-R0

## Packaging Information

| Packaging | Specifications      | Standard<br>Packing<br>Quantity |
|-----------|---------------------|---------------------------------|
| R0        | 180mm Embossed Tape | 3000                            |



MURATA's package technology expertise has enabled the development of the Chip CERALOCK.

High-density mounting is made possible by the small package and the elimination of the need for an external load capacitor.

#### Features

- 1. Oscillation circuits do not require external load capacitors.
- 2. Available for a wide frequency range.
- 3. Extremely small and have a low profile.
- 4. No adjustment is necessary for oscillation circuits.
- 5. Available for a wide temperature range.

1 of 2

#### Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued

without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering





# CSTCE16M9V53Z-R0

Note: This datasheet may be out of date. Please download the latest datasheet of CSTCE16M9V53Z-R0 from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en-gb/products/productdetail?partno=CSTCE16M9V53Z-R0

## Specifications

| Product Type                           | Ceramic Resonator<br>(CERALOCK) |
|--|---------------------------------|
| Series                                 | CSTCE_V                         |
| Frequency                              | 16.934MHz                       |
| Frequency Tolerance                    | +/-0.50% max.                   |
| Operating Temperature<br>Range         | -40°C~125°C                     |
| Frequency Shift by<br>Temperature      | +/-0.30% max.                   |
| Frequency Aging                        | +/-0.20% max.                   |
| Resonant Impedance (R1)                | 40ohm max.                      |
| Built-in Load Capacitance<br>(CL1/CL2) | 15pF                            |
| Shape                                  | SMD                             |
| Wash                                   | Not available                   |
| L x W (size)                           | 3.2x1.3mm                       |
| Mass                                   | 17mg                            |

2 of 2

#### Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued

without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.

