

Product Search Data Sheet

Note: This datasheet may be out of date.

Please download the latest datasheet of PV37W201C01B00 from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en-gb/products/productdetail?partno=PV37W201C01B00

# PV37W201C01B00










## Appearance & Shape







### **Features**

- Smaller volume (about one-third) than 25-turn potentiometer
- 2. Sealed construction protects the interior from dust and liquid, which achieves stable performance.
- 3. Available for ultrasonic cleaning after soldering.
- 4. Clutch mechanism prevents excessive wiper rotation.



## Packaging Information

| Packaging | Specifications | Standard<br>Packing<br>Quantity |
|-----------|----------------|---------------------------------|
| B00       | Bulk(Bag)      | 100                             |

1 of 3

#### Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

 $2. This \ data{sheet has only typical specifications because there is no \ space for \ detailed \ specifications.}$ 

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.





Note: This datasheet may be out of date.  $Please\ download\ the\ latest\ data sheet\ of\ PV37W201C01B00\ from\ the\ official\ website\ of\ Murata$ Manufacturing Co., Ltd.

http://www.murata.com/en-gb/products/productdetail?partno=PV37W201C01B00

# PV37W201C01B00



# **Specifications**

| Power Rating                               | 0.25W  |  |
|--|--|--|
| Shape                                      | Lead   |  |
| Maximum Working Voltage                    | 200Vdc   |  |
| Adjustment Direction                       | Тор  |  |
| Size                                       | 6mm  |  |
| Auto Adjustment                            | No   |  |
| Number of Turns (Effective Rotation Angle) | 12   |  |
| Mechanical Rotation Angle                  | -  |  |
| Total Resistance Value                     | 200Ω   |  |
| Total Resistance Value Tolerance           | ±10%   |  |
| Temperature Coefficient of Resistance      | ±150ppm/°C   |  |
| Resistance Taper                           | B (Linear)   |  |
| Contact Resistance Variation               | Less than 3% of total resistance value or 3ohm, whichever is greater |  |
| Residual Resistance                        | 2ohm max.  |  |
| Torque                                     | 21.2mN ⋅ m max.  |  |
| Measure Condition of RatedPower            | 85°C   |  |
| Operating Temperature<br>Range             | -55°C to 125°C   |  |
| Mass                                       | 0.34g  |  |

2 of 3

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.





# PV37W201C01B00


Note: This datasheet may be out of date.

Please download the latest datasheet of PV37W201C01B00 from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en-gb/products/productdetail?partno=PV37W201C01B00



## **Product Data**



### Constructions

3 of 3

#### Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.

