

**Product Search Data Sheet** 

Note: This datasheet may be out of date. Please download the latest datasheet of TZW4Z010A001B00 from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en-gb/products/productdetail?partno=TZW4Z010A001B00

# TZW4Z010A001B00










### Appearance & Shape







### **Features**

- 1. To meet high power application due to withstanding voltage
- 2. Extremely high self-resonant frequency. (More than 3GHz at rated C max.)
- 3. Typical application: Impedance matching for Cellular Base Station.
- 4. High Q value in more than VHF, UHF and Microwave bands. (More than 200 in 500MHz, C max.)
- 5. Available for pick and place machine. Possible thinner design due to 2.6mm low profile.
- 6. Non-electrical contact construction (rotor as middle electrode) provides high reliability.
- 7. Compact size: 4.2(W)x5.2(L)x2.6max.(H)mm.



## Packaging Information

Packaging	Specifications	Standard Packing Quantity
B00	Bulk(Bag)	100

1 of 3

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering





Note: This datasheet may be out of date. Please download the latest datasheet of TZW4Z010A001B00 from the official website of Murata  $\,$ Manufacturing Co., Ltd.

http://www.murata.com/en-gb/products/productdetail?partno=TZW4Z010A001B00

# TZW4Z010A001B00



# **Specifications**

Shape	SMD
Operating Temperature Range	-55°C to 125°C
Thickness	2.6mm
Thickness Tolerance	max.
Rated Voltage	250Vdc
Cmin.(max.)	0.4pF
Cmax.	1pF
Cmax. Tolerance	+50/-0%
Adjustment Direction	Тор
тс	NP0±150ppm/°C
Q	200min. at 500MHz, Cmax.
Withstanding Voltage	550Vdc
Insulation Resistance(min.)	10000ΜΩ
Torque	1.5 to 10.0mNm
Mass	0.15g

2 of 3

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.




Note: This datasheet may be out of date. Please download the latest datasheet of TZW4Z010A001B00 from the official website of Murata Manufacturing Co., Ltd.


http://www.murata.com/en-gb/products/productdetail?partno=TZW4Z010A001B00

# TZW4Z010A001B00




### **Product Data**





### Constructions





Temp. Coeff. Characteristics

Frequency Characteristics

3 of 3

- 1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.
- 2. This datasheet has only typical specifications because there is no space for detailed specifications.
- Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.

