

Note: This datasheet may be out of date. Please download the latest datasheet of CSTCC2M50G56Z-R0 from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en-gb/products/productdetail?partno=CSTCC2M50G56Z-R0

CSTCC2M50G56Z-R0










Applications

Unsuitable	Please be sure to read and comply with
Applications	these "Precautions for use."
Specific Applications	Consumer equipment
	Please refer to Our Website and
	specifications, etc. for information about
	the performance, functions, quality,
	management, and safety required for
	the above applications, and use
	Products after confirming the
	performance and reliability of the actual
	Product.



Appearance & Shape







Packaging Information

Packaging	Specifications	Standard Packing Quantity
R0	180mm Embossed Tape	2000



Features

MURATA's package technology expertise has enabled the development of the Chip CERALOCK. High-density mounting can be realized because of the small package and the elimination of the need for an external load capacitor.

Features

- 1. Oscillation circuits do not require external load capacitors.
- 2. Available in a wide frequency range.
- 3. Extremely small and have a low profile.
- 4. No adjustment is necessary for oscillation circuits.

1 of 2

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering





Floduct Search Data Shee

Note: This datasheet may be out of date.

Please download the latest datasheet of CSTCC2M50G56Z-R0 from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en-gb/products/productdetail?partno=CSTCC2M50G56Z-R0

CSTCC2M50G56Z-R0



Specifications

t Type Ceramic Resonator	
(CERALOCK)	
CSTCC_G	
ncy 2.500MHz	
ncy Tolerance +/-0.50% max.	
ing Temperature -40°C~125°C	
ncy Shift by -0.60 to +0.30%	
rature -0.00 to +0.30 %	
ncy Aging +/-0.30% max.	
ant Impedance (R1) 80ohm max.	
Load Capacitance	
L2) 47pr	
SMD	
Not available	
size) 7.2x3.0mm	
92mg	
Load Capacitance L2) SMD Not available 7.2x3.0mm	

2 of 2

Attention

1.This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.

