

Note: This datasheet may be out of date. Please download the latest datasheet of XDCAG38M850PGA00P0 from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en/products/productdetail?partno=XDCAG38M850PGA00P0

XDCAG38M850PGA00P0











Applications

Unsuitable	Please be sure to read and comply with	
Applications	these "Precautions for use."	
	Industrial Equipment	
	Please refer to Our Website and	
	specifications, etc. for information about	
Cassifia	the performance, functions, quality,	
Specific	management, and safety required for	
Applications	the above applications, and use	
	Products after confirming the	
	performance and reliability of the actual	
	Product.	



Appearance & Shape







Packaging Information

Packaging	Specifications	Standard Packing Quantity
P0	330mm Plastic Tape	3000



Features

Murata's Crystal Filter with original thin wafer design technology based on long experience and activity realizes high reliability and is widely used in various applications such as business radio.

1 of 3

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.





Note: This datasheet may be out of date. ${\it Please download the latest datasheet of XDCAG38M850PGA00P0 from the official website of Murata}$ Manufacturing Co., Ltd.

http://www.murata.com/en/products/productdetail?partno=XDCAG38M850PGA00P0

XDCAG38M850PGA00P0



Specifications

_		
Center Frequency	38.8500MHz	
Operating Temperature	-20°C to 70°C	
Range	-20 C 10 70 C	
Number of Pole	4	
3dB Bandwidth	±5.0kHzmin.	
Insertion Loss(max.)	5dB	
Ripple(max.)	1dB	
Stop Bandwidth	25kHzmax.	
Area of Stop Bandwidth	[45dB]	
Stop Band Attenuation(min.)	70dB	
Spurious Attenuation(min.)	40dB	
Termination Impedance	610ohm // 3.0pF [Cc=14.0pF]	
Mass	125.65mg	

2 of 3

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.







Note: This datasheet may be out of date. Please download the latest datasheet of XDCAG38M850PGA00P0 from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en/products/productdetail?partno=XDCAG38M850PGA00P0

XDCAG38M850PGA00P0








Frequency Characteristics

Spurious Response



Measurement Circuit

3 of 3

Attention

- 1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.
- 2. This datasheet has only typical specifications because there is no space for detailed specifications.
- Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.

