

Note: This datasheet may be out of date.

Please download the latest datasheet of PTGL07AS181M0N51A0 from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en/products/productdetail?partno=PTGL07AS181M0N51A0

## PTGL07AS181M0N51A0











### Appearance & Shape







(in mm)



### Packaging Information

| Packaging | Specifications | Standard Packing Quantity |
|-----------|----------------|---------------------------|
| A0        | Ammo Pack      | 1000                      |



#### **Features**

- 1. Protection against overcurrent situations
- 2. Automatic reset from protective trip mode
- 3. Space-saving
- 4. Various characteristics to meet a suitable resistance value.

1 of 3

#### Attention

- 1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.
- $2. This \ data{sheet has only typical specifications because there is no \ space for \ detailed \ specifications.}$
- Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.





#### Product Search Data Sheet

Note: This datasheet may be out of date.  $Please\ download\ the\ latest\ data sheet\ of\ PTGL07AS181M0N51A0\ from\ the\ official\ website\ of\ Murata$ Manufacturing Co., Ltd.

http://www.murata.com/en/products/productdetail?partno=PTGL07AS181M0N51A0

## PTGL07AS181M0N51A0



## **Specifications**

| Max. Voltage                         | 280V           |
|--------------------------------------|----------------|
| Resistance (25°C)                    | 180Ω           |
| Resistance Value Tolerance (at 25°C) | ±20%           |
| Max. Inrush Current(peak)            | 6.22A          |
| Max. Applying Time of Inrush         | 10ms           |
| Operating Temperature<br>Range       | -40°C to 105°C |
| D- Outer Dimension                   | 7.8mm          |
| Thickness                            | 6mm            |
| F- Lead Space                        | 5mm            |
| d- Lead Diameter                     | 0.5mm          |
| Shape                                | Lead           |
| Mass                                 | 0.75g          |
| MSL                                  | N              |

2 of 3

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.




# Note: This datasheet may be out of date. Please download the latest datasheet of PTGL07AS181M0N51A0 from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en/products/productdetail?partno=PTGL07AS181M0N51A0

## PTGL07AS181M0N51A0



### **Product Data**



Resistance-Temperature Charac.

3 of 3

#### Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.

