

Product Search Data Sheet

Note: This datasheet may be out of date. Please download the latest datasheet of CFWLA455KJFA-B0 from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en-sg/products/productdetail?partno=CFWLA455KJFA-B0

CFWLA455KJFA-B0










Applications

| Unsuitable | Please be sure to read and comply with |
|--------------|--|
| Applications | these "Precautions for use." |
| | Consumer equipment |
| | Please refer to Our Website and |
| | specifications, etc. for information about |
| Specific | the performance, functions, quality, |
| Specific | management, and safety required for |
| Applications | the above applications, and use |
| | Products after confirming the |
| | performance and reliability of the actual |
| | Product. |



Appearance & Shape







Packaging Information

| Packaging | Specifications | Standard Packing Quantity |
|-----------|----------------|---------------------------------|
| -B0 | Bulk | 150 |



Features

Ceramic filter CFWLAseries are low profile high selectivity ceramic filters, which use 6 elements in ladder form. They are best suitable to high-class transceivers, cordless telephones and amateur radios.

Features

- 1. Low profile, high selectivity
- 2. Available bandwidths are B to J as standard
- 3. Easily mountable on any PC board
- 4. Operating temperature range: -20 to +80 (degrees C), Storage temperature range: -40 to +85 (degrees C)

1 of 3

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering





Product Search Data Sheet

Note: This datasheet may be out of date. ${\it Please download the latest datasheet of CFWLA455KJFA-B0 from the official website of Murata}$ Manufacturing Co., Ltd.

http://www.murata.com/en-sg/products/productdetail?partno=CFWLA455KJFA-B0

CFWLA455KJFA-B0



Specifications

| Operating Temperature Range | -20°C to 80°C |
|-----------------------------|------------------------------|
| Shape | Lead |
| Elements | 6 |
| Center Frequency | 455.0kHz |
| Nominal Center Value | Yes |
| 6dB Bandwidth | fn±2.0kHzmin. |
| Stop Bandwidth | 7.5kHz |
| Area of Stop Bandwidth | [within 50dB] |
| Stop Band Attenuation | 60dB[within fn±100kHz] |
| Insertion Loss | 7.0dB[at minimum loss point] |
| Ripple | 2.0dB[within fn±1.5kHz] |
| Input/Output Impedance | 2000Ω |
| Mass | 690mg |

2 of 3

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.



Product Search Data Sheet


Note: This datasheet may be out of date.


Please download the latest datasheet of CFWLA455KJFA-B0 from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en-sg/products/productdetail?partno=CFWLA455KJFA-B0

CFWLA455KJFA-B0








Frequency Characteristics

Spurious Response



Rg+R1=R2=Input/Output Impedance

Measurement Circuit

3 of 3

Attention

- 1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.
- $2. This \ data{sheet has only typical specifications because there is no \ space for \ detailed \ specifications.}$
- Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.

