

Product Search Data Sheet

CSTCR4M09G53-R0


In Production Recommended RoHS REACH

Applications

Unsuitable	Please be sure to read and comply with	
Applications	these "Precautions for use."	
Specific Applications	Consumer equipment,Industrial	
	equipment except for transportation &	
	facility & energy equipment,Medical	
	equipment [GHTF A/B],Mobile	
	Electronics	
	Please refer to Our Website and	
	specifications, etc. for information about	
	the performance, functions, quality,	
	management, and safety required for	
	the above applications, and use	
	Products after confirming the	
	performance and reliability of the actual	
	Product.	

Appearance & Shape





Note: This datasheet may be out of date. Please download the latest datasheet of CSTCR4M09G53-R0 from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en-sg/products/productdetail?partno=CSTCR4M09G53-R0

Packaging Information

	Packaging	Specifications	Standard Packing Quantity
	R0	180mm Embossed Tape	3000



MURATA's package technology expertise has enabled the development of the Chip CERALOCK. High-density mounting can be realized because of the small package and the elimination of the need for an external load capacitor.

Features

- 1. Oscillation circuits do not require external load capacitors.
- 2. Available in a wide frequency range.
- 3. Extremely small and have a low profile.
- 4. No adjustment is necessary for oscillation circuits.



Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued

without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering





CSTCR4M09G53-R0

Note: This datasheet may be out of date. Please download the latest datasheet of CSTCR4M09G53-R0 from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en-sg/products/productdetail?partno=CSTCR4M09G53-R0

Specifications

Ceramic Resonator Product Type (CERALOCK) Series CSTCR G Frequency 4.096MHz Frequency Tolerance +/-0.50% max. **Operating Temperature** -20°C~80°C Range Frequency Shift by +/-0.20% max. Temperature Frequency Aging +/-0.10% max. Resonant Impedance (R1) 60ohm max. Built-in Load Capacitance 15pF (CL1/CL2) Shape SMD Wash Not available L x W (size) 4.5x2.0mm Mass 29mg

2 of 2

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued

without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.

