

Product Search Data Sheet

IRA-S230ST01

In Production Recommended RoHS REACH

Applications

| Unsuitable | Please be sure to read and comply with | |
|--------------------------|--|--|
| Applications | these "Precautions for use." | |
| | Consumer equipment | |
| | Please refer to Our Website and | |
| | specifications, etc. for information about | |
| Specific | the performance, functions, quality, | |
| Specific Applications | management, and safety required for | |
| | the above applications, and use | |
| | Products after confirming the | |
| | performance and reliability of the actual | |
| | Product. | |
| Recommended | Intrusion detection, Security Equipment, | |
| Applications | Light | |

Note: This datasheet may be out of date. Please download the latest datasheet of IRA-S230ST01 from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en-sg/products/productdetail?partno=IRA-S230ST01

Packaging Information

| Packaging | | Standard Packing Quantity |
|-----------|-----|---------------------------------|
| - | Box | 100 |




Excellent Sensitivity & S/N ratio (Signal/Noise) **Excellent Quality**



Appearance & Shape





(in mm)

1 of 3

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued

without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.





IRA-S230ST01

Note: This datasheet may be out of date. Please download the latest datasheet of IRA-S230ST01 from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en-sg/products/productdetail?partno=IRA-S230ST01



Shape Lead TO-5(φ9.2x4.7mm) Dimensions Output Type Analog Electrode (2.0x1.0mm)x2 Responsivity(typ.) 4.6mV Supply Voltage Range 2V to 15V Field of View theta1=theta2=45deg. **Operating Temperature** -40°C to 70°C Range Storage Temperature Range -40°C to 85°C

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued

without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.

2 of 3

Product Search Data Sheet




INNOVATOR IN ELECTRONICS


Note: This datasheet may be out of date. Please download the latest datasheet of IRA-S230ST01 from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en-sg/products/productdetail?partno=IRA-S230ST01


Product Data



(in mm)



Pyroelectric Elements(Electrode Dimension)



Test system of Responsivity

Optical Filter characteristics

3 of 3

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued

without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.

