



Note: This datasheet may be out of date. Please download the latest datasheet of NCP03XM222J05RL from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en-sg/products/productdetail?partno=NCP03XM222J05RL

# NCP03XM222J05RL










## **Applications**

Unsuitable	Please be sure to read and comply with	
Applications	these "Precautions for use."	
	Consumer equipment,Medical	
	equipment [GHTF A/B]	
	Please refer to Our Website and	
	specifications, etc. for information about	
Specific	the performance, functions, quality,	
Applications	management, and safety required for	
	the above applications, and use	
	Products after confirming the	
	performance and reliability of the actual	
	Product.	



## Appearance & Shape







## Packaging Information

Packaging	Specifications	Standard Packing Quantity
RL	180mm Paper Tape	15000



#### **Features**

- 1. Excellent solderability and high stability in environment
- 2. Excellent long time aging stability
- 3. High accuracy in resistance and B-Constant
- 4. Reflow soldering possible
- 5. Lead is not contained in the product.
- 6. UL/cULcertified product.(UL1434, File No. E137188)

1 of 3

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.





### Product Search Data Sheet

Note: This datasheet may be out of date.  $Please\ download\ the\ latest\ data sheet\ of\ NCP03XM222J05RL\ from\ the\ official\ website\ of\ Murata$ Manufacturing Co., Ltd.

http://www.murata.com/en-sg/products/productdetail?partno=NCP03XM222J05RL

# NCP03XM222J05RL



# **Specifications**

Resistance (25°C)	2.2kΩ	
, ,	2.2132	
Resistance Value Tolerance	±5%	
(at 25°C)		
B-Constant (25/50°C)	3500K	
B-Constant (25/50°C)	+1%	
Tolerance	1170	
B-Constant(25/80°C)	3539K	
(Reference Value)	000011	
B-Constant(25/85°C)	3545K	
(Reference Value)	00-1010	
B-Constant(25/100°C)	3560K	
(Reference Value)	000011	
Max. Voltage	5V	
Maximum Operating Current	0.213mA	
(25°C)	0.213mA	
Typical Dissipation Constant	1mW/°C	
(25°C)	IIIIVV/ C	
Operating Temperature	-40°C to 125°C	
Range	-40 C to 125 C	
Size Code (in mm)	0.6x0.3mm	
Size Code (in inch)	0.2x0.1inch	
Shape	SMD	
Mass	0.00026g	
MSL	1	

2 of 3

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.



Note: This datasheet may be out of date.


Please download the latest datasheet of NCP03XM222J05RL from the official website of Murata Manufacturing Co., Ltd.


http://www.murata.com/en-sg/products/productdetail?partno=NCP03XM222J05RL

# NCP03XM222J05RL




## **Product Data**





### Resistance-Temperature Characteristics



Max. Voltage, Max. Operating Voltage/Current Reduction Curve

Temperature Error Characteristics

3 of 3

#### Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.

