



Note: This datasheet may be out of date. Please download the latest datasheet of CSTNE8M00GH5L000R0 from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en-sg/products/productdetail?partno=CSTNE8M00GH5L000R0

CSTNE8M00GH5L000R0












Applications

Unsuitable	Please be sure to read and comply with	
Applications	these "Precautions for use."	
Specific Applications	Consumer equipment,Industrial equipment except for transportation & facility & energy equipment,Medical equipment [GHTF A/B],Mobile Electronics Please refer to Our Website and specifications, etc. for information about the performance, functions, quality, management, and safety required for the above applications, and use Products after confirming the performance and reliability of the actual Product.	



Appearance & Shape







Packaging Information

Packaging	Specifications	Standard Packing Quantity
R0	180mm Embossed Tape	3000



Features

MURATA's frequency adjustment and packaging technology expertise has enabled the development of the chip CERALOCK.

Features

- 1. Oscillation circuits do not require external load capacitors.
- 2. Available for a wide frequency range.
- 3. Extremely small and have a low profile.
- 4. No adjustment is necessary for oscillation circuits.
- 5. Stable supply is ensured due to not using precious metal(Palladium).

1 of 2

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering





Note: This datasheet may be out of date. $Please\ download\ the\ latest\ data sheet\ of\ CSTNE8M00GH5L000R0\ from\ the\ official\ website\ of\ Murata$ Manufacturing Co., Ltd.

http://www.murata.com/en-sg/products/productdetail?partno=CSTNE8M00GH5L000R0

CSTNE8M00GH5L000R0



Specifications

	Ceramic Resonator	
Product Type		
	(CERALOCK)	
Series	CSTNE_GH5L	
Frequency	8.000MHz	
Frequency Tolerance	+/-0.07% max.	
Operating Temperature	-40°C~85°C	
Range	-40 C~85 C	
Frequency Shift by	1/0.440/ =====	
Temperature	+/-0.11% max.	
Frequency Aging	+/-0.07% max.	
rioquonoy riginig	17 0.07 70 Max.	
Resonant Impedance (R1)	40ohm max.	
Built-in Load Capacitance		
(CL1/CL2)	33pF	
(CL I/CLZ)		
Shape	SMD	
Wash	Not available	
YYGGII	Trot available	
L x W (size)	3.2x1.3mm	
Mass	11.73mg	

2 of 2

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.

