



Note: This datasheet may be out of date.

Please download the latest datasheet of NCP15XC220J03RC from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en-us/products/productdetail?partno=NCP15XC220J03RC

# NCP15XC220J03RC










# **Applications**

Unsuitable	Please be sure to read and comply with	
Applications	these "Precautions for use."	
Specific Applications	Consumer equipment	
	Please refer to Our Website and	
	specifications, etc. for information about	
	the performance, functions, quality,	
	management, and safety required for	
	the above applications, and use	
	Products after confirming the	
	performance and reliability of the actual	
	Product.	



# Appearance & Shape







# Packaging Information

Packaging	Specifications	Standard Packing Quantity
RC	180mm Paper Tape	10000



### **Features**

- 1. Excellent solderability and high stability in environment
- 2. Excellent long time aging stability
- 3. High accuracy in resistance and B-Constant
- 4. Reflow soldering possible
- 5. Same B-constant in the same resistance in the three sizes (0805 size / 0603 size / 0402 size)

Easy to use smaller size in the circuits

- 6. Lead is not contained in the product.
- 7. UL/cULcertified product.(UL1434, File No. E137188)

1 of 2

#### Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.





### Product Search Data Sheet

Note: This datasheet may be out of date. Please download the latest datasheet of NCP15XC220J03RC from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en-us/products/productdetail?partno=NCP15XC220J03RC

# NCP15XC220J03RC



# **Specifications**

D : ( (05%C)	000	
Resistance (25°C)	22Ω	
Resistance Value Tolerance	±5%	
(at 25°C)		
B-Constant (25/50°C)	3100K	
B-Constant (25/50°C)	±3%	
Tolerance		
B-Constant(25/80°C)	3126K	
(Reference Value)		
B-Constant(25/85°C)	3128K	
(Reference Value)		
B-Constant(25/100°C)	3136K	
(Reference Value)		
Max. Voltage	5V	
Maximum Operating Current	2.132mA	
(25°C)		
Typical Dissipation Constant	1mW/°C	
(25°C)	Tillivi C	
Operating Temperature	-40°C to 125°C	
Range		
Size Code (in mm)	1.0x0.5mm	
Size Code (in inch)	0.4x0.2inch	
Shape	SMD	
Mass	0.0012g	
MSL	1	

2 of 2

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.

