


Product Search Data Sheet

TZB4P400BA10B00

Discontinued RoHS REACH

Appearance & Shape





Note: This datasheet may be out of date. Please download the latest datasheet of TZB4P400BA10B00 from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en/products/productdetail?partno=TZB4P400BA10B00



- 1. Miniature rectangular shape: 4.0(W)x4.5(L)x3.0(H)mm.
- 2. Color coded case facilitates identification of capacitance range.
- 3. Designed for automatic placement in surface mount applications.
- Designed to withstand flux baths and solder baths (with cover film type).
- 5. Can be temporarily attached to PCB with adhesives (Terminal style Aand B).
- 6. Can be reflow and flow (with cover film type) soldering method.
- 7. Stable characteristics over a wide frequency range. (Resonant frequency: 1000MHz min. / 6pF)

Packaging Information

Packaging	Specifications	Standard Packing Quantity
B00	Bulk(Bag)	500

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued

without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering





TZB4P400BA10B00

Note: This datasheet may be out of date. Please download the latest datasheet of TZB4P400BA10B00 from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en/products/productdetail?partno=TZB4P400BA10B00

Specifications

Shape	SMD
Operating Temperature Range	-25°C to 85°C
Thickness	3mm
Thickness Tolerance	±0.2
Rated Voltage	100Vdc
Cmin.(max.)	8.5pF
Cmax.	40pF
Cmax. Tolerance	+50/-0%
Adjustment Direction	Тор
тс	N1200±500ppm/°C
Q	300min. at 1MHz, Cmax
Withstanding Voltage	220Vdc
Insulation Resistance(min.)	10000ΜΩ
Torque	1.5 to 9.8mNm
Stator/Case Color	Yellow
Mass	0.15g

2 of 3

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued

without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.



Product Search Data Sheet





TZB4P400BA10B00

Note: This datasheet may be out of date. Please download the latest datasheet of TZB4P400BA10B00 from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en/products/productdetail?partno=TZB4P400BA10B00







Constructions

Temp. Coeff. Characteristics

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued

without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.



3 of 3