

Note: If you have not downloaded this document from our official website, please note that the information provided may not be the most current. Please download the latest datasheet of LLM3225-121J from the official website of Murata

http://www.murata.com/en/products/productdetail?partno=LLM3225-121J

# LLM3225-121J




## Applications

Unsuitable	Please be sure to read and comply with
Applications	these "Precautions for use."
	Consumer equipment,Medical
	equipment [GHTF A/B/C] except for
	implant & surgery & auto injector,
	Industrial equipment except for
	transportation & facility & energy
	equipment
Specific	Please refer to Our Website and
Applications	specifications, etc. for information about
	the performance, functions, quality,
	management, and safety required for
	the above applications, and use
	Products after confirming the
	performance and reliability of the actual
	Product.
Recommended	Cancumer equipment
Applications	Consumer equipment

### Appearance & Shape







Rated current is specified when the decrease of the initial inductance value at 10%. Or rated current is specified when temperature of the inductor is raised 20°C by DC current. Whichever is smaller.



	Packaging	Specifications	Standard	
			Packing	
			Quantity	
	-	180Embossed Tape	2000	

Mass (typ.)		
1 piece	0.04g	

1 of 3

### Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued

without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.





## LLM3225-121J

Note: If you have not downloaded this document from our official website, please note that the information provided may not be the most current.

Please download the latest datasheet of LLM3225-121J from the official website of Murata

http://www.murata.com/en/products/productdetail?partno=LLM3225-121J



### L size 3.2±0.2mm W size 2.5±0.2mm T size 2.4mm Size code inch (mm) 1210 (3225) Inductance 120µH±5% Inductance Test Frequency 0.796MHz Max. of DC resistance 10Ω **Operating Temperature** Range (Self-temperature -40°C to 85°C rise is included) Class of magnetic shield Non-Shielded Q(min.) 20 0.796MHz **Q** Test Frequency Self resonance frequency 8MHz (min.) Brand Murata Rated Current 65mA Series LLM3225

2 of 3

### Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued

without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.

Product Search Data Sheet




Note: If you have not downloaded this document from our official website, please note that the information provided may not be the most current.

Please download the latest datasheet of LLM3225-121J from the official website of Murata

http://www.murata.com/en/products/productdetail?partno=LLM3225-121J

# LLM3225-121J





**Q-Frequency Characteristics** 

3 of 3

### Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued

without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.

