

Note: This datasheet may be out of date.

Please download the latest datasheet of LQH55DN1R0M03# from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en/products/productdetail?partno=LQH55DN1R0M03%23

"#"at the end indicates the package specification code.

#### Large Current











# < List of part numbers with package codes > LQH55DN1R0M03K LQH55DN1R0M03L




### **Applications**

| Unsuitable   | Please be sure to read and comply with     |  |
|--------------|--|--|
| Applications | these "Precautions for use."               |  |
|              | Consumer equipment,Medical                 |  |
|              | equipment [GHTF A/B/C] except for          |  |
|              | implant & surgery & auto injector,         |  |
|              | Industrial equipment except for            |  |
|              | transportation & facility & energy         |  |
|              | equipment                                  |  |
| Specific     | Please refer to Our Website and            |  |
| Applications | specifications, etc. for information about |  |
|              | the performance, functions, quality,       |  |
|              | management, and safety required for        |  |
|              | the above applications, and use            |  |
|              | Products after confirming the              |  |
|              | performance and reliability of the actual  |  |
|              | Product.                                   |  |
| Recommended  | Canaumar aguinment                         |  |
| Applications | Consumer equipment                         |  |



### Appearance & Shape







### **Notices**

When rated current is applied to the products, inductance will be within ±40% of initial inductance value. When rated current is applied to the products, the temperature rise caused by self-generated heat shall be limited to 40°C max.

1 of 4

#### Attentior

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.





Note: This datasheet may be out of date.

Please download the latest datasheet of LQH55DN1R0M03# from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en/products/productdetail?partpo=LOH55DN1R0M03%2

"#"at the end indicates the package specification code.



### References

| Packaging | Specifications   | Standard Packing Quantity |
|-----------|------------------|---------------------------|
| К         | 330Embossed Tape | 1500                      |
| L         | 180Embossed Tape | 350                       |

| Mass (typ.) |  |       |
|-------------|--|-------|
| 1 piece     |  | 0.48g |

2 of 4

#### Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

 $2. This \ data{sheet has only typical specifications because there is no space for \ detailed \ specifications.}$ 

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.





Note: This datasheet may be out of date.

Please download the latest datasheet of LQH55DN1R0M03# from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en/products/productdetail?partno=LQH55DN1R0M03%2

"#"at the end indicates the package specification code.



## **Specifications**

| L size   | 5.7±0.3mm     |
|--|---------------|
| W size   | 5.0±0.3mm     |
| T size   | 4.7±0.3mm     |
| Size code inch (mm)  | 2220 (5750)   |
| Inductance   | 1μH±20%       |
| Inductance Test Frequency  | 1MHz          |
| Rated current (Itemp) (Based on Temperature rise)                  | 4.0A          |
| Max. of DC resistance  | 0.0266Ω       |
| DC resistance  | 0.019Ω±40%    |
| Operating Temperature Range(Self-temperature rise is not included) | -40°C to 80°C |
| Class of magnetic shield   | Non-Shielded  |
| Self resonance frequency (min.)                                    | 150MHz        |
| Brand  | Murata        |
| Series   | LQH55DN_03    |

3 of 4

#### Attention

1.This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.





Note: This datasheet may be out of date.


Please download the latest datasheet of LQH55DN1R0M03# from the official website of Murata Manufacturing Co., Ltd.


http://www.murata.com/en/products/productdetail?partno=LQH55DN1R0M03%2

"#"at the end indicates the package specification code.



### Characteristic Data





Impedance - Current Characteristics

Impedance - Frequency Characteristics

4 of 4

#### Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering

