

Product Search Data Sheet

CFUKG455KE4X-R0

Discontinued RoHS


HS REACH

Applications

Unsuitable	Please be sure to read and comply with
Applications	these "Precautions for use."
Specific Applications	Consumer equipment
	Please refer to Our Website and
	specifications, etc. for information about
	the performance, functions, quality,
	management, and safety required for
	the above applications, and use
	Products after confirming the
	performance and reliability of the actual
	Product.



Appearance & Shape




Note: This datasheet may be out of date. Please download the latest datasheet of CFUKG455KE4X-R0 from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en/products/productdetail?partno=CFUKG455KE4X-R0

Packaging Information

	Packaging	Specifications	Standard Packing Quantity
	-R0	180mm Embossed Tape	450



The CFUKG_X series is comprised of small, highperformance, thin (4.0mm) filters consisting of 4 ceramic elements. The filters exhibit an extremely flat GDT characteristic combined with a narrow bandwidth. The filters are recommended for narrow band digital communication applications.

Features

1. The filters are mountable by automatic placers.

2. The filters can be refl ow soldered and withstand washing.

3. They are slim, at only 4.0mm maximum thickness, and have a small mounting area (7.5x6.0mm) enabling flexible PCB design. 4. The bandwidth ranges from E to H.

5. Operating temperature range: -20 to +80 (degrees C), Storage temperature range: -40 to +85 (degrees C)

1 of 3

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued

without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering





CFUKG455KE4X-R0

Note: This datasheet may be out of date. Please download the latest datasheet of CFUKG455KE4X-R0 from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en/products/productdetail?partno=CFUKG455KE4X-R0

Specifications

Operating Temperature -20°C to 80°C Range SMD Shape 4 Elements **Center Frequency** 455.0kHz Center Frequency Tolerance ±1.5kHz Nominal Center Value No 6dB Bandwidth fn±7.5kHzmin. Stop Bandwidth 17.5kHz Area of Stop Bandwidth [within 40dB] Stop Band Attenuation 27dB[within fn±100kHz] Insertion Loss 6.0dB[at minimum loss point] Ripple 1.0dB[within fn±5kHz] **GDT** Deviation 25.0µs[within fn±5kHz] Input/Output Impedance 1500Ω 504mg Mass

2 of 3

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued

without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.









CFUKG455KE4X-R0

Note: This datasheet may be out of date. Please download the latest datasheet of CFUKG455KE4X-R0 from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en/products/productdetail?partno=CFUKG455KE4X-R0


Product Data





Frequency Characteristics

Spurious Response



Measurement Circuit

3 of 3

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued

without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.

