

Product Search Data Sheet

PVG5A100C03B00


Note: This datasheet may be out of date. Please download the latest datasheet of PVG5A100C03B00 from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en-gb/products/productdetail?partno=PVG5A100C03B00

Discontinued RoHS REACH

Appearance & Shape







- 1. Sealed construction protects the interior from dust and liquid, which achieves stable performance.
- 2. Available with reflow soldering method
- 3. Available for ultrasonic cleaning after soldering
- 4. Clutch mechanism prevents excessive wiper rotation.
- 5. Both Top and side adjustment directions
- 6. Ultra smaller volume (1/5-1/2) than leaded multi-turn potentiometer.

Packaging Information

| Packaging | | Standard Packing Quantity |
|-----------|-----------|---------------------------------|
| B00 | Bulk(Bag) | 100 |

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued

without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering





PVG5A100C03B00

Note: This datasheet may be out of date. Please download the latest datasheet of PVG5A100C03B00 from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en-gb/products/productdetail?partno=PVG5A100C03B00

Specifications

| Power Rating | 0.25W | |
|---|--|--|
| Shape | SMD | |
| Maximum Working Voltage | 300Vdc | |
| Adjustment Direction | Тор | |
| Size | 5mm | |
| Auto Adjustment | No | |
| Number of Turns (Effective Rotation Angle) | 11 | |
| Mechanical Rotation Angle | - | |
| Total Resistance Value | 10Ω | |
| Total Resistance Value Tolerance | ±10% | |
| Temperature Coefficient of Resistance | ±150ppm/°C | |
| Resistance Taper | B (Linear) | |
| Contact Resistance Variation | Less than 3% of total resistance value or 3ohm, whichever is greater | |
| Residual Resistance | Less than 1% of total resistance value or 2ohm, whichever is greater | |
| Torque | 17.6mN · m max. | |
| Measure Condition of RatedPower | 70°C | |
| Operating Temperature Range | -55℃ to 125℃ | |
| Mass | 0.18g | |

2 of 3

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued

without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.



Product Search Data Sheet




Note: This datasheet may be out of date. Please download the latest datasheet of PVG5A100C03B00 from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en-gb/products/productdetail?partno=PVG5A100C03B00

PVG5A100C03B00





Constructions

3 of 3

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued

without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.

