

Note: This datasheet may be out of date. Please download the latest datasheet of SFSKA6M00CF00-R3 from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en-gb/products/productdetail?partno=SFSKA6M00CF00-R3

SFSKA6M00CF00-R3










Applications

Unsuitable	Please be sure to read and comply with	
Applications	these "Precautions for use."	
Specific Applications	Consumer equipment	
	Please refer to Our Website and	
	specifications, etc. for information about	
	the performance, functions, quality,	
	management, and safety required for	
	the above applications, and use	
	Products after confirming the	
	performance and reliability of the actual	
	Product.	



Appearance & Shape







Packaging Information

Packaging	Specifications	Standard Packing Quantity
-R3 330mm Embossed Tape		3000



Features

SMD ceramic filter SFSKA_CF is a small and thin SMD filter sealed with a metal cap. Recommended for LCD-TVs, and small and thin tuners.

Features

- 1. High attenuation outside bandwidth.
- 2. Small and thin package.
- 3. Reflow-solderable.

1 of 3

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.





Product Search Data Sheet

SFSKA6M00CF00-R3

Note: This datasheet may be out of date. $Please\ download\ the\ latest\ data sheet\ of\ SFSKA6M00CF00-R3\ from\ the\ official\ website\ of\ Murata$ Manufacturing Co., Ltd.

http://www.murata.com/en-gb/products/productdetail?partno=SFSKA6M00CF00-R3



Specifications

Operating Temperature Range	-20°C to 80°C
Shape	SMD
Elements	1
Center Frequency	6.000MHz
Nominal Center Value	Yes
3dB Bandwidth	fn±60kHzmin.
Stop Bandwidth	600kHz
Spurious Attenuation	25dB[within 0 to fn]
Insertion Loss	6.0dBmax.
Input/Output Impedance	470Ω
Mass	137mg

2 of 3

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.



Product Search Data Sheet


Note: This datasheet may be out of date. Please download the latest datasheet of SFSKA6M00CF00-R3 from the official website of Murata Manufacturing Co., Ltd.


http://www.murata.com/en-gb/products/productdetail?partno=SFSKA6M00CF00-R3

SFSKA6M00CF00-R3




Product Data





Frequency Characteristics

Spurious Response



R1+Rg=R2=470Ω ±5%, Rg=50Ω C2=10pF (Including stray capacitance and Input capacitance of RF Voltmeter) E1: S.S.G. Output voltage

Measurement Circuit

3 of 3

- 1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.
- 2. This datasheet has only typical specifications because there is no space for detailed specifications.
- Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.

