

Note: This datasheet may be out of date. Please download the latest datasheet of #A914BYW-470M=P3 from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en-gb/products/productdetail?partno=%23A914BYW-470M%3dP3

#A914BYW-470M=P3
















Applications

Unsuitable	Please be sure to read and comply with
Applications	these "Precautions for use."
	Consumer equipment,Medical
	equipment [GHTF A/B/C] except for
	implant & surgery & auto injector,
	Industrial equipment except for
	transportation & facility & energy
	equipment
Specific	Please refer to Our Website and
Applications	specifications, etc. for information about
	the performance, functions, quality,
	management, and safety required for
	the above applications, and use
	Products after confirming the
	performance and reliability of the actual
	Product.
Recommended	Consumer equipment
Applications	Consumer equipment



Appearance & Shape







Notices

Rated current (Isat) is specified when the decrease of the initial inductance value at 30%. Rated current (Itemp) is specified when temperature of the inductor is raised 40°C by DC current.



References

	Specifications	Standard
Packaging		Packing
		Quantity
=P3	330Embossed Tape	2000

Mass (typ.)		
	1 piece	0.138g

1 of 3

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.





#A914BYW-470M=P3

Note: This datasheet may be out of date.

Please download the latest datasheet of #A914BYW-470M=P3 from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en-gb/products/productdetail?partno=%23A914BYW-470M%3dP3



Specifications

Laine	5.0	
L size	5.2mm	
W size	5.2mm	
T size	2.0mm	
Size code inch (mm)	2020 (5252)	
Inductance	47μH±20%	
Inductance Test Frequency	0.1MHz	
Rated current (Isat) (Based on Inductance change)	360mA	
Rated current (Itemp)		
(Based on Temperature rise)	380mA	
Max. of DC resistance	0.73Ω	
Operating Temperature		
Range (Self-temperature	-40°C to 85°C	
rise is included)		
Class of magnetic shield	Shielded (Ferrite Core)	
Brand	Murata	
Series	D52LC	

2 of 3

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.



Product Search Data Sheet


Note: This datasheet may be out of date. Please download the latest datasheet of #A914BYW-470M=P3 from the official website of Murata Manufacturing Co., Ltd.


http://www.murata.com/en-gb/products/productdetail?partno=%23A914BYW-470M%3dP3

#A914BYW-470M=P3



Characteristic Data





Impedance - Current Characteristics

Temperature Increase Characteristic

3 of 3

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.

