

Product Search Data Sheet

#A921CY-100M=P3

Note: This datasheet may be out of date. Please download the latest datasheet of #A921CY-100M=P3 from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en-gb/products/productdetail?partno=%23A921CY-100M%3dP3




## Applications

Unsuitable	Please be sure to read and comply with
Applications	these "Precautions for use."
	Consumer equipment,Medical
	equipment [GHTF A/B/C] except for
	implant & surgery & auto injector,
	Industrial equipment except for
	transportation & facility & energy
	equipment
Specific	Please refer to Our Website and
Applications	specifications, etc. for information about
	the performance, functions, quality,
	management, and safety required for
	the above applications, and use
	Products after confirming the
	performance and reliability of the actual
	Product.
Recommended	Canaumar aquinment
Applications	Consumer equipment

### Appearance & Shape







Rated current (Isat) is specified when the decrease of the initial inductance value at 30%. Rated current (Itemp) is specified when temperature of the inductor is raised 40°C by DC current.



		Standard
Packaging	Specifications	Packing
		Quantity
=P3	330Embossed Tape	1500

Mass (typ.)	
1 piece	0.358g



#### Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued

without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.





# #A921CY-100M=P3

Note: This datasheet may be out of date. Please download the latest datasheet of #A921CY-100M=P3 from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en-gb/products/productdetail?partno=%23A921CY-100M%3dP3

### Specifications

L size	6.0±0.3mm
W size	6.0±0.3mm
T size	3.0mm
Size code inch (mm)	2424 (6060)
Inductance	10µH±20%
Inductance Test Frequency	0.1MHz
Rated current (Isat) (Based on Inductance change)	1140mA
Rated current (Itemp) (Based on Temperature rise)	1910mA
Max. of DC resistance	0.059Ω
DC resistance	0.049Ω+20%/-30%
Operating Temperature Range (Self-temperature rise is included)	-40℃ to 85℃
Class of magnetic shield	Shielded (Ferrite Core)
Brand	Murata
Series	D63LCB

2 of 3

#### Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued

without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.









# #A921CY-100M=P3

Note: This datasheet may be out of date. Please download the latest datasheet of #A921CY-100M=P3 from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en-gb/products/productdetail?partno=%23A921CY-100M%3dP3

Characteristic Data





Impedance - Current Characteristics

Temperature Increase Characteristic

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued

without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.



3 of 3