

### Product Search Data Sheet

Note: This datasheet may be out of date.

Please download the latest datasheet of UEI15-050-Q48P-C from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en-gb/products/productdetail?partno=UEI15-050-Q48P-C

## UEI15-050-Q48P-C









### **Applications**

Unsuitable	Please be sure to read and comply with
Applications	these "Precautions for use."
	Consumer equipment,Industrial
	Equipment
	Please refer to Our Website and
	specifications, etc. for information about
Specific	the performance, functions, quality,
Applications	management, and safety required for
	the above applications, and use
	Products after confirming the
	performance and reliability of the actual
	Product.



### **Features**

15 Watt, 5V, Single Output Isolated DC-DC Converter, Wide 18-75V Input Range, 1x1 package, Positive Polarity



# Appearance & Shape



1 of 2

#### Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.





### Product Search Data Sheet

#### Note: This datasheet may be out of date. Please download the latest datasheet of UEI15-050-Q48P-C from the official website of Murata $\,$ Manufacturing Co., Ltd.

http://www.murata.com/en-gb/products/productdetail?partno=UEI15-050-Q48P-C

# UEI15-050-Q48P-C



## **Specifications**

Output power (W)Max	15W
Vin(V)	18V to 75V
Vin(V)typ	48V
Vout(V)	5V
Vout(V)typ	5V
LineRegulation (%)	0.05%
LoadRegulation (%)	0.06%
Isolation Voltage (V)	2250V
Efficiency (%)	86%
Size(mm)W	24.4mm
Size(mm)L	27.9mm
Size(mm)T	8.4mm
Operatingtemperature(degC)	-40°C to 85°C
Outputs (#)	1
lout(A)Max	3A
Form	1 x 1
Package	DIP
Productseries	UEI
Product Series Features	Isolated Wide Input Range 15- Watt DC-DC Converters
Safety Approval	These devices meet UL/CSA60950 and IEC/EN60950 safety standards, including BASIC insulation requirements. Q48 models are CE marked (meet the requirements of LVD).
Brand	Murata Power Solutions

2 of 2

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.

