

Product Search Data Sheet

Note: This datasheet may be out of date. Please download the latest datasheet of RHS7G2A181J0K1H01B from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en-gb/products/productdetail?partno=RHS7G2A181J0K1H01B


RHS7G2A181J0K1H01B



Applications

Unsuitable	Please be sure to read and comply with	
Applications	these "Precautions for use."	
	Automotive powertrain/safety equipment,	
	Automotive infotainment/comfort	
	equipment,Medical equipment [GHTF	
	A/B/C] except for implant equipment	
	Please refer to Our Website and	
Specific	specifications, etc. for information about	
Applications	the performance, functions, quality,	
	management, and safety required for	
	the above applications, and use	
	Products after confirming the	
	performance and reliability of the actual	
	Product.	

Appearance & Shape





HF(Halogen Free), Derating5



References

		Standard	
Packaging		Packing	
		Quantity	
В	Bulk(Bag)	500	

Mass (typ.)		
1 piece	0.1g	

1 of 3

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued

without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.





RHS7G2A181J0K1H01B

Note: This datasheet may be out of date. Please download the latest datasheet of RHS7G2A181J0K1H01B from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en-gb/products/productdetail?partno=RHS7G2A181J0K1H01B

Specifications

L size or Outer diameter D	3.9mm max.	
Width	3.5mm max.	
T size	2.6mm max.	
Lead spacing F	5.0±0.8mm	
Lead diameter d	0.5±0.05mm	
Paint dripping e	Up to the end of crimp	
Capacitance	180pF ±5%	
Rated voltage	100Vdc	
Temperature characteristics	CCG(MURATA)	
Temperature range of temperature characteristics	-55°C to 200°C	
Operating Temperature Range	-55°C to 200°C	
тс	-55°C to 25°C: 0+30/- 72ppm/°C 25°C to 125°C: 0±30ppm/°C 125°C to 200°C: 0+72/-30ppm/°C	
W1 size	6.0mm max.	

2 of 3

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued

without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.





Product Search Data Sheet


Note: This datasheet may be out of date. Please download the latest datasheet of RHS7G2A181J0K1H01B from the official website of Murata Manufacturing Co., Ltd.


http://www.murata.com/en-gb/products/productdetail?partno=RHS7G2A181J0K1H01B

RHS7G2A181J0K1H01B



Characteristic Data





Capacitance - temperature characteristics

Impedance - frequency characteristics

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued

without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.



3 of 3