

GA355QR7GF332KW01L

Note: This datasheet may be out of date.

Please download the latest datasheet of GA355QR7GF332KW01# from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en-gb/products/productdetail?partno=GA355QR7GF332KW01%23

"#"at the end indicates the package specification code.













< List of part numbers with package codes > GA355QR7GF332KW01L GA355QR7GF332KW01K



Applications

Unsuitable	Please be sure to read and comply with	
Applications	these "Precautions for use."	
	. ,	
	Products after confirming the	
	Ĭ	
	performance and reliability of the actual	
	Product.	




Notices

X1/Y2 Class Certified Products



Appearance & Shape







References

	Specifications	Standard
Packaging		Packing
		Quantity
L	180Embossed Tape	1000
К	330Embossed Tape	4000

Mass (typ.)		
1 piece	220.0mg	

1 of 2

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.





GA355QR7GF332KW01L

Note: This datasheet may be out of date.

Please download the latest datasheet of GA355QR7GF332KW01# from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en-gb/products/productdetail?partno=GA355QR7GF332KW01%23

"#"at the end indicates the package specification code.



Specifications

Length	5.7±0.4mm
Width	5.0±0.4mm
Thickness	1.5+0/-0.3mm
Capacitance	3300pF ±10%
Distance between external terminals g	4.0mm min.
External terminal size e	0.3mm min.
Operating Temperature Range	-55°C to 125°C
Rated Voltage	250Vac(r.m.s.)
Size code in inch(mm)	2220 (5750M)
Capacitance change rate	±15.0%
Temperature characteristics (complied standard)	X7R(EIA)
Temperature range of temperature characteristics	-55°C to 125°C

2 of 2

Attention

1.This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.

