

KRM55QR71H226KH13L

Note: If you have not downloaded this document from our official website, please note that the information provided may not be the most current.

Please download the latest datasheet of KRM55QR71H226KH13# from the official website of Murata

http://www.murata.com/en-qb/products/productdetail?partno=KRM55QR71H226KH13%23

"#"at the end indicates the package specification code.

















< List of part numbers with package codes > KRM55QR71H226KH13L KRM55QR71H226KH13K



Applications

Unsuitable	Please be sure to read and comply with	
Applications	these "Precautions for use."	
	Consumer equipment,Industrial	
	Equipment,Mobile Electronics,Medical	
	equipment [GHTF A/B/C] except for	
	implant equipment	
	Please refer to Our Website and	
Specific	specifications, etc. for information about	
Applications	the performance, functions, quality,	
	management, and safety required for	
	the above applications, and use	
	Products after confirming the	
	performance and reliability of the actual	
	Product.	



References


	Specifications	Standard
Packaging		Packing
		Quantity
L	180Embossed Tape	400
К	330Embossed Tape	1000

Mass (typ.)	
1 piece	0.46g



Appearance & Shape





1 of 2

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

 $2. This \ data{sheet has only typical specifications because there is no \ space for \ detailed \ specifications.}$

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.





KRM55QR71H226KH13L

Note: If you have not downloaded this document from our official website, please note that the information provided may not be the most current.

Please download the latest datasheet of KRM55QR71H226KH13# from the official website of Murata

"#"at the end indicates the package specification code.



Specifications

Length	6.1±0.4mm	
Width	5.3±0.2mm	
Thickness	3.7±0.2mm	
Capacitance	22μF ±10%	
Metal terminal width e	1.2±0.2mm	
Operating Temperature Range	-55°C to 125°C	
Rated Voltage	50Vdc	
Capacitance change rate	±15%	
Temperature characteristics	X7R(EIA)	
(complied standard)	, , , , , , , , , , , , , , , , , , ,	
Temperature range of	-55°C to 125°C	
temperature characteristics		

2 of 2

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.

