

Product Search Data Sheet

Note: This datasheet may be out of date. Please download the latest datasheet of NTSD1XV103FPB40 from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en-gb/products/productdetail?partno=NTSD1XV103FPB40

NTSD1XV103FPB40










Applications

Unsuitable	Please be sure to read and comply with	
Applications	these "Precautions for use."	
Specific Applications	Industrial Equipment	
	Please refer to Our Website and	
	specifications, etc. for information about	
	the performance, functions, quality,	
	management, and safety required for	
	the above applications, and use	
	Products after confirming the	
	performance and reliability of the actual	
	Product.	



Appearance & Shape





Type	L (mm)
NTSD1_FPB30	30
NTSD1_FPB40	40
NTSD1_FPB50	50



Packaging Information

Packaging	Specifications	Standard Packing Quantity
-	Bulk(Bag)	200



Features

- 1. Electric insulation on lead wire
- 2. Excellent bending resistance due to suitable hardness of surface coating
- 3. Easy handling due to most suitable hardness of surface of coating
- 4. +/-1% of resistance and +/-0.5% of B-Constant is realized due to technical advantages of the material and manufacturing process.

1 of 3

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.





Product Search Data Sheet

Note: This datasheet may be out of date. Please download the latest datasheet of NTSD1XV103FPB40 from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en-gb/products/productdetail?partno=NTSD1XV103FPB40

NTSD1XV103FPB40



Specifications


Resistance (25°C)	10kΩ	
` ′	10022	
Resistance Value Tolerance	±1%	
(at 25°C)		
B-Constant (25/50°C)	3900K	
B-Constant (25/50°C)	±0.5%	
Tolerance		
B-Constant(25/80°C)	3930K	
(Reference Value)		
B-Constant(25/85°C)	3934K	
(Reference Value)	000 111	
B-Constant(25/100°C)	3944K	
(Reference Value)		
Maximum Operating Current	0.12mA	
(25°C)	0.12117	
Rated Electric Power (25°C)	15.0mW	
Typical Dissipation Constant	1.5mW/°C	
(25°C)	1.011107	
Operating Temperature	-40°C to 125°C	
Range		
Thermal Time Constant	7s	
Lead Shape	Insulation type	
Shape	Lead	
Mass	0.13g	
MSL	N	

2 of 3

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.






NTSD1XV103FPB40

Note: This datasheet may be out of date.

Please download the latest datasheet of NTSD1XV103FPB40 from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en-gb/products/productdetail?partno=NTSD1XV103FPB40





Temperature Tolenrance-Temperature Characteristics

3 of 3

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.

