

Product Search Data Sheet

Note: If you have not downloaded this document from our official website, please note that the information provided may not be the most current.

Please download the latest datasheet of CSBFB1M00J58-B0 from the official website of Murata

http://www.murata.com/en-qb/products/productdetail?partno=CSBFB1M00J58-Bi

CSBFB1M00J58-B0










Applications

Unsuitable	Please be sure to read and comply with
Applications	these "Precautions for use."
	Consumer equipment
	Please refer to Our Website and
	specifications, etc. for information about
Specific	the performance, functions, quality,
Specific	management, and safety required for
Applications	the above applications, and use
	Products after confirming the
	performance and reliability of the actual
	Product.



Appearance & Shape







Packaging Information

Packaging	Specifications	Standard Packing Quantity
В0	Bulk	1000



Features

MURATA's original package technologies have enabled the development of the kHz band CERALOCK. The series is perfect in miniature remote control units and AV modules. CERALOCK can be reflow soldered and mounted by automatic placement equipment.

Features

- 1. Withstands reflow soldering.
- 2. Compatible with automatic placement equipment.
- 3. No adjustment is necessary for oscillation circuits.

1 of 2

Attention

- 1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.
- $2. This \ data{sheet has only typical specifications because there is no \ space for \ detailed \ specifications.}$

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.





Product Search Data Sheet

Note: If you have not downloaded this document from our official website, please note that the information provided may not be the most current.

Please download the latest datasheet of CSBFB1M00J58-B0 from the official website of Murata

CSBFB1M00J58-B0



Specifications

Product Type	Ceramic Resonator
Froduct Type	(CERALOCK)
Series	CSBFB_J
Frequency	1000.0kHz
Frequency Tolerance	+/-0.50% max.
Operating Temperature	-20°C~80°C
Range	-20 0 00 0
Frequency Shift by	+/-0.30% max.
Temperature	+7-0.30 % IIIax.
Frequency Aging	+/-0.30% max.
Resonant Impedance (R1)	100ohm max.
Shape	SMD
Wash	available
L x W (size)	6.0x5.0mm

2 of 2

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.

