

### Product Search Data Sheet

Note: If you have not downloaded this document from our official website, please note that the information provided may not be the most current. Please download the latest datasheet of PV12T204A01B00 from the official website of Murata

## PV12T204A01B00










## Appearance & Shape







### **Features**

- 1. The unique inner gear system recognizes the position of the center of the shaft of the potentiometer.
- 2. Sealed construction protects the interior from dust and liquid, which achieves stable performance.
- 3. Available for ultrasonic cleaning after soldering.
- 4. Clutch mechanism prevents excessive wiper rotation.



## Packaging Information

| Packaging | Specifications | Standard<br>Packing<br>Quantity |
|-----------|----------------|---------------------------------|
| B00       | Bulk(Bag)      | 50                              |

1 of 3

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.





Note: If you have not downloaded this document from our official website, please note that the information provided may not be the most current.

Please download the latest datasheet of PV12T204A01B00 from the official website of Murata

# PV12T204A01B00



# **Specifications**

| Power Rating                               | 0.5W   |  |
|--|--|--|
| Shape                                      | Lead   |  |
| Maximum Working Voltage                    | 300Vdc   |  |
| Adjustment Direction                       | Side   |  |
| Size                                       | 7mm  |  |
| Auto Adjustment                            | No   |  |
| Number of Turns (Effective Rotation Angle) | 4  |  |
| Mechanical Rotation Angle                  | -  |  |
| Total Resistance Value                     | 200kΩ  |  |
| Total Resistance Value Tolerance           | ±10%   |  |
| Temperature Coefficient of Resistance      | ±100ppm/°C   |  |
| Resistance Taper                           | B (Linear)   |  |
| Contact Resistance Variation               | Less than 3% of total resistance value or 3ohm, whichever is greater |  |
| Residual Resistance                        | 2ohm max.  |  |
| Torque                                     | 14.7mN ⋅ m max.  |  |
| Measure Condition of RatedPower            | 70°C   |  |
| Operating Temperature<br>Range             | -55°C to 125°C   |  |
| Mass                                       | 0.8g   |  |

2 of 3

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.






# PV12T204A01B00

Note: If you have not downloaded this document from our official website, please note that the information provided may not be the most current.

Please download the latest datasheet of PV12T204A01B00 from the official website of Murata

http://www.murata.com/en-qb/products/productdetail?partno=PV12T204A01B0





Constructions

3 of 3

### Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.

