Product Search Data Sheet



PVA2A103A01R00

Note: If you have not downloaded this document from our official website, please note that the information provided may not be the most current.


Please download the latest datasheet of PVA2A103A01R00 from the official website of Murata

http://www.murata.com/en-gb/products/productdetail?partno=PVA2A103A01R00



Appearance & Shape







- 1. Ultra-small and thin external dimensions of 2.2(W)x2.75(L)x0.90 max.(T)mm.
- 2. For the terminal attachment method of construction that uses neither solder nor adhesives, good solderability and terminal attachment intensity are realized.
- 3. Because of multi-contact wiper structure, PVA2 has a stable characteristics (low noise).
- PVA2 series does not use a solder, flux or cleaning solvent, so they are environmentally friendly products.
- 5. Heat resistance performance enables high temperature peak reflow soldering.

Packaging Information

Packaging	Specifications	Standard Packing Quantity
R00	180mm Embossed Tape	3000

1 of 3

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued

without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering





PVA2A103A01R00

Note: If you have not downloaded this document from our official website, please note that the information provided may not be the most current.

Please download the latest datasheet of PVA2A103A01R00 from the official website of Murata

http://www.murata.com/en-gb/products/productdetail?partno=PVA2A103A01R00



Power Rating 0.1W SMD Shape 50Vdc Maximum Working Voltage Adjustment Direction Тор Size 2mm Yes Auto Adjustment Number of Turns (Effective 1(260°±10°) Rotation Angle) Mechanical Rotation Angle Endless **Total Resistance Value** 10kΩ Total Resistance Value ±25% Tolerance Temperature Coefficient of ±250ppm/°C Resistance **Resistance Taper** B (Linear) 3% max. of nominal total Contact Resistance Variation resistance value 4% max. of nominal total **Residual Resistance** resistance value 0.5 to 9.8mN · m Torque Measure Condition of 70°C RatedPower Operating Temperature -55°C to 125°C Range Mass 0.01g

2 of 3

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued

without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.

Product Search Data Sheet




PVA2A103A01R00

Note: If you have not downloaded this document from our official website, please note that the information provided may not be the most current.

 $\label{eq:please} Please \ \text{download} \ the \ latest \ data sheet \ of \ PVA2A103A01R00 \ from \ the \ of \ ficial \ website \ of \ Murata$

http://www.murata.com/en-gb/products/productdetail?partno=PVA2A103A01R00





Constructions

3 of 3

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued

without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.

