

Product Search Data Sheet

Note: This datasheet may be out of date. Please download the latest datasheet of NCP21XM472J03RA from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en/products/productdetail?partno=NCP21XM472J03RA

NCP21XM472J03RA










Applications

Unsuitable	Please be sure to read and comply with	
Applications	these "Precautions for use."	
	Consumer equipment	
	Please refer to Our Website and	
	specifications, etc. for information about	
Specific	the performance, functions, quality,	
Specific Applications	management, and safety required for	
	the above applications, and use	
	Products after confirming the	
	performance and reliability of the actual	
	Product.	



Appearance & Shape







Packaging Information

Packaging	Specifications	Standard Packing Quantity
RA	180mm Embossed Tape	4000



Features

- 1. Excellent solderability and high stability in environment
- 2. Excellent long time aging stability
- 3. High accuracy in resistance and B-constant
- 4. Flow / Reflow soldering possible
- 5. Same B-Constant in the same resistance in the three sizes (0805 size / 0603 size / 0402 size)

Easy to use smaller size in the circuits

- 6. Lead is not contained in the product.
- 7. UL/cULcertified product. (UL1434, File No. E137188)

1 of 3

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

(in mm)

- 2. This datasheet has only typical specifications because there is no space for detailed specifications.
- Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.





Product Search Data Sheet

Note: This datasheet may be out of date. $Please\ download\ the\ latest\ data sheet\ of\ NCP21XM472J03RA\ from\ the\ official\ website\ of\ Murata$ Manufacturing Co., Ltd.

http://www.murata.com/en/products/productdetail?partno=NCP21XM472J03RA

NCP21XM472J03RA



Specifications

Resistance (25°C)	4.7kΩ	
, ,	4.7 (\$2	
Resistance Value Tolerance	±5%	
(at 25°C)		
B-Constant (25/50°C)	3500K	
B-Constant (25/50°C)	±3%	
Tolerance	15070	
B-Constant(25/80°C)	3539K	
(Reference Value)	000011	
B-Constant(25/85°C)	3545K	
(Reference Value)	334310	
B-Constant(25/100°C)	3560K	
(Reference Value)	COOCIC	
Max. Voltage	5V	
Maximum Operating Current	0.206mA	
(25°C)	0.206MA	
Typical Dissipation Constant	2mW/°C	
(25°C)	ZITIVV/ C	
Operating Temperature	-40°C to 125°C	
Range	1-40 C to 123 C	
Size Code (in mm)	2.0x1.25mm	
Size Code (in inch)	0.8x0.5inch	
Shape	SMD	
Mass	0.0094g	
MSL	1	

2 of 3

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.



Note: This datasheet may be out of date.


 $Please\ download\ the\ latest\ data sheet\ of\ NCP21XM472J03RA\ from\ the\ official\ website\ of\ Murata$ Manufacturing Co., Ltd.

http://www.murata.com/en/products/productdetail?partno=NCP21XM472J03RA


NCP21XM472J03RA



Product Data



Resistance-Temperature Characteristics



Maximum Operating Voltage Reduction Characteristics

3 of 3

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.

