

### Product Search Data Sheet

Note: This datasheet may be out of date. Please download the latest datasheet of PVG5A103C03B00 from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en/products/productdetail?partno=PVG5A103C03B00

## PVG5A103C03B00










### Appearance & Shape







### **Features**

- 1. Sealed construction protects the interior from dust and liquid, which achieves stable performance.
- 2. Available with reflow soldering method
- 3. Available for ultrasonic cleaning after soldering
- 4. Clutch mechanism prevents excessive wiper rotation.
- 5. Both Top and side adjustment directions
- 6. Ultra smaller volume (1/5-1/2) than leaded multi-turn potentiometer.



### Packaging Information

| Packaging | Specifications | Standard<br>Packing<br>Quantity |
|-----------|----------------|---------------------------------|
| B00       | Bulk(Bag)      | 100                             |

1 of 3

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering





Note: This datasheet may be out of date. Please download the latest datasheet of PVG5A103C03B00 from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en/products/productdetail?partno=PVG5A103C03B00

# PVG5A103C03B00



## **Specifications**

| Power Rating                               | 0.25W  |  |
|--|--|--|
| Shape                                      | SMD  |  |
| Maximum Working Voltage                    | 300Vdc   |  |
| Adjustment Direction                       | Тор  |  |
| Size                                       | 5mm  |  |
| Auto Adjustment                            | No   |  |
| Number of Turns (Effective Rotation Angle) | 11   |  |
| Mechanical Rotation Angle                  | -  |  |
| Total Resistance Value                     | 10kΩ   |  |
| Total Resistance Value<br>Tolerance        | ±10%   |  |
| Temperature Coefficient of Resistance      | ±150ppm/°C   |  |
| Resistance Taper                           | B (Linear)   |  |
| Contact Resistance Variation               | Less than 3% of total resistance value or 3ohm, whichever is greater |  |
| Residual Resistance                        | Less than 1% of total resistance value or 20hm, whichever is greater |  |
| Torque                                     | 17.6mN ⋅ m max.  |  |
| Measure Condition of RatedPower            | 70°C   |  |
| Operating Temperature<br>Range             | -55°C to 125°C   |  |
| Mass                                       | 0.18g  |  |

2 of 3

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.






# PVG5A103C03B00

Note: This datasheet may be out of date.

Please download the latest datasheet of PVG5A103C03B00 from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en/products/productdetail?partno=PVG5A103C03B00





Constructions

3 of 3

### Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.

