


Product Search Data Sheet

TZY2R200AC01B00

Discontinued RoHS REACH

Appearance & Shape





Note: This datasheet may be out of date. Please download the latest datasheet of TZY2R200AC01B00 from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en/products/productdetail?partno=TZY2R200AC01B00



- 1. Small and thin size with external dimensions of 2.5(W)x3.2(L)x1.25max.(H)mm.
- 2. New shape of cover can improve the flux invasion compared with current products.
- 3. Improvement of the adhesion between rotor and stator leads to superior stability.
- 4. Unique construction with no plastic material provides superior soldering
- heat resistance to maintain excellent characteristic performance after reflow soldering.

Packaging Information

| Packaging | Specifications | Standard Packing Quantity |
|-----------|----------------|---------------------------------|
| B00 | Bulk(Bag) | 500 |

1 of 3

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued

without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.





TZY2R200AC01B00

Note: This datasheet may be out of date. Please download the latest datasheet of TZY2R200AC01B00 from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en/products/productdetail?partno=TZY2R200AC01B00

Specifications

| Shape | SMD | |
|--------------------------------|------------------------|--|
| Operating Temperature Range | -25°C to 85°C | |
| Thickness | 1.25mm | |
| Thickness Tolerance | max. | |
| Rated Voltage | 25Vdc | |
| Cmin.(max.) | 4.5pF | |
| Cmax. | 20pF | |
| Cmax. Tolerance | +100/-0% | |
| Adjustment Direction | Тор | |
| ТС | N750±500ppm/°C | |
| Q | 500min. at 1MHz, Cmax. | |
| Withstanding Voltage | 55Vdc | |
| Insulation Resistance(min.) | 10000ΜΩ | |
| Torque | 0.7 to 4.9mNm | |
| Mass | 0.032g | |

2 of 3

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued

without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.



Product Search Data Sheet





TZY2R200AC01B00

Note: This datasheet may be out of date. Please download the latest datasheet of TZY2R200AC01B00 from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en/products/productdetail?partno=TZY2R200AC01B00

Product Data





Temp. Coeff. Characteristics

3 of 3

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued

without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.

