

BEI15-050-Q12P-C

Note: This datasheet may be out of date.

Please download the latest datasheet of BEI15-050-Q12P-C from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en/products/productdetail?partno=BEI15-050-Q12P-C







Applications

| Unsuitable | Please be sure to read and comply with |
|--------------|--|
| Applications | these "Precautions for use." |
| | Consumer equipment,Industrial |
| | Equipment |
| | Please refer to Our Website and |
| | specifications, etc. for information about |
| Specific | the performance, functions, quality, |
| Applications | management, and safety required for |
| | the above applications, and use |
| | Products after confirming the |
| | performance and reliability of the actual |
| | Product. |



Features

 $\pm 5 \text{V}, \pm 1500 \text{mA}, \text{Dual Output Isolated 1"x1" DC-DC Converter, 9-36V Input Range, Positive Logic, Through-Hole}$



Appearance & Shape



1 of 2

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.





Product Search Data Sheet

Note: This datasheet may be out of date. Please download the latest datasheet of BEI15-050-Q12P-C from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en/products/productdetail?partno=BEI15-050-Q12P-C

BEI15-050-Q12P-C



Specifications

| Output power (W)Max | 15W |
|----------------------------|--|
| Vin(V) | 9V to 36V |
| Vin(V)typ | 24V |
| Vout(V) | 5V |
| Vout(V)typ | 5V |
| LineRegulation (%) | -0.25% to 0.25% |
| LoadRegulation (%) | -0.25% to 0.25% |
| Isolation Voltage (V) | 2000V |
| Efficiency (%) | 84.5% |
| Size(mm)W | 24.4mm |
| Size(mm)L | 27.9mm |
| Size(mm)T | 8.4mm |
| Operatingtemperature(degC) | -40°C to 85°C |
| Outputs (#) | 2 |
| lout(A)Max | 1.5A |
| Form | 1 x 1 |
| Package | DIP |
| Productseries | BEI |
| Product Series Features | Isolated Wide Input Bipolar 15- Watt DC-DC Converters |
| lout2(A)Max | -1.5A |
| Vout2 (V) | -5V |
| Vout2 (V)typ | -5V |
| Brand | Murata Power Solutions |

2 of 2

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.

