

Product Search Data Sheet

Note: If you have not downloaded this document from our official website, please note that the information provided may not be the most current.

Please download the latest datasheet of UWE-12/10-Q48NB-C from the official website of Murata

UWE-12/10-Q48NB-C









Applications

Unsuitable	Please be sure to read and comply with
Applications	these "Precautions for use."
	Consumer equipment,Industrial
	Equipment
	Please refer to Our Website and
	specifications, etc. for information about
Specific	the performance, functions, quality,
Applications	management, and safety required for
	the above applications, and use
	Products after confirming the
	performance and reliability of the actual
	Product.



Features

12V, 10A, Single Output Isolated 1/8 Brick DC-DC Converter, 18-75V Input Range, Negative polarity, Baseplate



Appearance & Shape



1 of 2

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.





Note: If you have not downloaded this document from our official website, please note that the information provided may not be the most current.

Please download the latest datasheet of UWE-12/10-Q48NB-C from the official website of Murata

UWE-12/10-Q48NB-C



Output power (W)Max	120W
Vin(V)	18V to 75V
Vin(V)typ	48V
Vout(V)	12V
Vout(V)typ	12V
LineRegulation (%)	0.15%
LoadRegulation (%)	0.075%
Isolation Voltage (V)	2250V
Efficiency (%)	91.5%
Size(mm)W	58.42mm
Size(mm)L	22.86mm
Size(mm)T	12.8mm
Operatingtemperature(degC)	-40°C to 85°C
Outputs (#)	1
lout(A)Max	10A
Form	1/8 Brick
Package	DIP
Productseries	UWE
Product Series Features	Quarter-brick DOSA- Compatible, Isolated DC-DC Converters
Safety Approval	These devices are designed to meet UL/CSA60950 and IEC/EN60950 safety standards, including BASIC insulation requirements. Q48 models are CE marked (meet the

Brand	Murata Power Solutions
-------	------------------------

2 of 2

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.

requirements of LVD).

