



Note: This datasheet may be out of date.

Please download the latest datasheet of CSTCR4M00G53U-R0 from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en/products/productdetail?partno=CSTCR4M00G53U-R0

CSTCR4M00G53U-R0












Applications

Unsuitable	Please be sure to read and comply with	
Applications	these "Precautions for use."	
Specific Applications	Consumer equipment,Industrial equipment except for transportation & facility & energy equipment,Medical equipment [GHTF A/B],Mobile Electronics Please refer to Our Website and specifications, etc. for information about the performance, functions, quality, management, and safety required for the above applications, and use Products after confirming the performance and reliability of the actual Product.	



Appearance & Shape





Packaging Information

Packaging	Specifications	Standard Packing Quantity
R0 180mm Embossed Tape 3000		3000



Features

MURATA's package technology expertise has enabled the development of the Chip CERALOCK. High-density mounting can be realized because of the small package and the elimination of the need for an external load capacitor.

Features

- 1. Oscillation circuits do not require external load capacitors.
- 2. Available in a wide frequency range.
- 3. Extremely small and have a low profile.
- 4. No adjustment is necessary for oscillation circuits.

1 of 2

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering





Product Search Data Sheet

Note: This datasheet may be out of date. $Please\ download\ the\ latest\ data sheet\ of\ CSTCR4M00G53U-R0\ from\ the\ official\ website\ of\ Murata$ Manufacturing Co., Ltd.

http://www.murata.com/en/products/productdetail?partno=CSTCR4M00G53U-R0

CSTCR4M00G53U-R0



Specifications

Product Type Ceramic Resonator (CERALOCK) Series CSTCR_G Frequency 4.000MHz Frequency Tolerance +/-0.50% max. Operating Temperature Range Frequency Shift by Temperature Frequency Aging +/-0.20% max. Frequency Aging +/-0.10% max. Resonant Impedance (R1) Built-in Load Capacitance (CL1/CL2) Shape SMD Wash Not available L x W (size) 4.5x2.0mm			
Series CSTCR_G Frequency 4.000MHz Frequency Tolerance +/-0.50% max. Operating Temperature Range -20°C~80°C Frequency Shift by +/-0.20% max. Frequency Aging +/-0.10% max. Resonant Impedance (R1) 45ohm max. Built-in Load Capacitance (CL1/CL2) Shape SMD Wash Not available L x W (size) 4.5x2.0mm	Draduct Type	Ceramic Resonator	
Frequency 4.000MHz Frequency Tolerance +/-0.50% max. Operating Temperature Range Frequency Shift by Temperature Frequency Aging +/-0.20% max. Frequency Aging +/-0.10% max. Resonant Impedance (R1) Built-in Load Capacitance (CL1/CL2) Shape SMD Wash Not available L x W (size) 4.5x2.0mm	Product Type	(CERALOCK)	
Frequency Tolerance +/-0.50% max. Operating Temperature Range -20°C~80°C +/-0.20% max. Frequency Shift by +/-0.20% max. Frequency Aging +/-0.10% max. Resonant Impedance (R1) 45ohm max. Built-in Load Capacitance (CL1/CL2) 15pF Shape SMD Wash Not available L x W (size) 4.5x2.0mm	Series	CSTCR_G	
Operating Temperature Range Frequency Shift by Temperature Frequency Aging +/-0.20% max. Frequency Aging +/-0.10% max. Resonant Impedance (R1) Built-in Load Capacitance (CL1/CL2) Shape SMD Wash Not available L x W (size) -20°C~80°C +/-0.20% max. 15pF SMD 45ohm max. Not available	Frequency	4.000MHz	
Range Frequency Shift by Temperature Frequency Aging +/-0.20% max. Frequency Aging +/-0.10% max. Resonant Impedance (R1) Built-in Load Capacitance (CL1/CL2) Shape SMD Wash Not available L x W (size) -20°C~80°C +/-0.20% max. 15pF Somm	Frequency Tolerance	+/-0.50% max.	
Range Frequency Shift by Temperature Frequency Aging +/-0.20% max. Frequency Aging +/-0.10% max. Resonant Impedance (R1) Built-in Load Capacitance (CL1/CL2) Shape SMD Wash Not available L x W (size) 4.5x2.0mm	Operating Temperature	-20°C~80°C	
Temperature +/-0.20% max. Frequency Aging +/-0.10% max. Resonant Impedance (R1) 45ohm max. Built-in Load Capacitance (CL1/CL2) 15pF Shape SMD Wash Not available L x W (size) 4.5x2.0mm	Range	1 20 0 00 0	
Temperature Frequency Aging +/-0.10% max. Resonant Impedance (R1) 450hm max. Built-in Load Capacitance (CL1/CL2) 15pF Shape SMD Wash Not available L x W (size) 4.5x2.0mm	Frequency Shift by		
Resonant Impedance (R1) Built-in Load Capacitance (CL1/CL2) Shape SMD Wash Not available L x W (size) 4.5x2.0mm	Temperature	+/-0.20% max.	
Built-in Load Capacitance (CL1/CL2) Shape SMD Wash Not available L x W (size) 4.5x2.0mm	Frequency Aging	+/-0.10% max.	
(CL1/CL2) 15pF Shape SMD Wash Not available L x W (size) 4.5x2.0mm	Resonant Impedance (R1)	45ohm max.	
Shape SMD Wash Not available L x W (size) 4.5x2.0mm	Built-in Load Capacitance	15pF	
Wash Not available L x W (size) 4.5x2.0mm	(CL1/CL2)	Topi	
L x W (size) 4.5x2.0mm	Shape	SMD	
	Wash	Not available	
	L x W (size)	4.5x2.0mm	
Mass 29mg	Mass	29mg	

2 of 2

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.

