



Please download the latest datasheet of XRCTD48M000NXQ2ER0 from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en/products/productdetail?partno=XRCTD48M000NXQ2ER0

Note: This datasheet may be out of date.

XRCTD48M000NXQ2ER0










Applications

Unsuitable	Please be sure to read and comply with		
Applications	these "Precautions for use."		
Specific Applications	Consumer equipment		
	Please refer to Our Website and		
	specifications, etc. for information about		
	the performance, functions, quality,		
	management, and safety required for		
	the above applications, and use		
	Products after confirming the		
	performance and reliability of the actual		
	Product.		



Appearance & Shape







Packaging Information

Packaging		Standard Packing Quantity
R0	180mm Plastic Tape	3000



Features

Based on Murata's excellent package technology and high grade quartz crystal elements, achieving small size and high accuracy crystal unit.

Features

- 1. The series is available in the applications to be necessary for high accuracy frequency.
- 2. The crystal unit is extremerly small size (1210), and contribute to reduction in mounting area.
- 3. The series complies to RoHS directive, being lead-free (phase 3).

1 of 2

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.





Note: This datasheet may be out of date. Please download the latest datasheet of XRCTD48M000NXQ2ER0 from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en/products/productdetail?partno=XRCTD48M000NXQ2ER0

XRCTD48M000NXQ2ER0



Specifications

Product Type	Crystal Unit
Series	XRCTD
Туре	MCR1210
Frequency	48.0000MHz
Frequency Tolerance	+/-40ppm max. (Total)
Total Frequency Tolerance	+/-40ppm max.
Operating Temperature Range	-30°C~85°C
Frequency Aging	+/-1ppm max./year
Equivalent Series Resistance (ESR)	40ohm max.
Drive Level (DL)	100μW max
Load Capacitance (Cs)	9pF
Shape	SMD
Wash	Not available (Please be sure to consult with our sales representative or engineer whenever and prior to using the products.)
L x W (size)	1.2x1.0mm
Mass	1.5mg

2 of 2

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.

