Note: This datasheet may be out of date.
Please download the latest datasheet of RHEL81H684K2A2H03B from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en/products/productdetail?partno=RHEL81H684K2A2H03B

RHEL81H684K2A2H03B

In Production | AEC-Q200 | RoHS | REACH | 150 °C max. | Low acoustic noise | Deflecting crack | Soldering crack | Flow OK | Welding

Applications


Unsuitable Applications	Please be sure to read and comply with these "Precautions for use."
Specific Applications	Automotive powertrain/safety equipment, Automotive infotainment/comfort equipment,Medical equipment [GHTF A/B/C] except for implant equipment Please refer to Our Website and specifications, etc. for information about the performance, functions, quality, management, and safety required for the above applications, and use Products after confirming the performance and reliability of the actual Product.

Notices

HF(Halogen Free)

Appearance & Shape





References

Packaging	Specifications	Standard Packing Quantity
B	Bulk(Bag)	500

Mass (typ.)	
1 piece	0.17g

Attention
1.This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.
2.This datasheet has only typical specifications because there is no space for detailed specifications.
Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.

Note: This datasheet may be out of date.
Please download the latest datasheet of RHEL81H684K2A2H03B from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en/products/productdetail?partno=RHEL81H684K2A2H03B

RHEL81H684K2A2H03B

Specifications

L size or Outer diameter D	5.5mm max.
Width	4.0mm max.
T size	3.15mm max.
Lead spacing F	2.5±0.8mm
Lead diameter d	0.5±0.05mm
Paint dripping e	1.5mm max.
Capacitance	0.68μF ±10%
Rated voltage	50Vdc
Temperature characteristics	X8L(MURATA)
Capacitance change rate	+15/-40%
Temperature range of temperature characteristics	-55℃ to 150℃
Operating Temperature Range	-55℃ to 150℃

Attention
1.This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.
2.This datasheet has only typical specifications because there is no space for detailed specifications.
Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.


Note: This datasheet may be out of date.
Please download the latest datasheet of RHEL81H684K2A2H03B from the official website of Murata Manufacturing Co., Ltd.


http://www.murata.com/en/products/productdetail?partno=RHEL81H684K2A2H03B


RHEL81H684K2A2H03B


Characteristic Data

The charts below may show another part number which shares its characteristics.











Attention
1.This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.
2.This datasheet has only typical specifications because there is no space for detailed specifications.
Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.

Note: This datasheet may be out of date.
Please download the latest datasheet of RHEL81H684K2A2H03B from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en/products/productdetail?partno=RHEL81H684K2A2H03B

RHEL81H684K2A2H03B





Attention
1.This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.
2.This datasheet has only typical specifications because there is no space for detailed specifications.
Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.