

Product Search Data Sheet

## LDM182G5005CC001


In Production Recommended RoHS REACH

### Applications

Unsuitable	Please be sure to read and comply with
Applications	these "Precautions for use."
Specific Applications	Consumer equipment,Industrial Equipment,Medical equipment [GHTF A/B],Mobile Electronics Please refer to Our Website and specifications, etc. for information about the performance, functions, quality, management, and safety required for the above applications, and use
	Products after confirming the performance and reliability of the actual Product.
Recommended Applications	Consumer equipment,Industrial Equipment,Medical equipment [GHTF A/B],Mobile Electronics



### Appearance & Shape



Note: This datasheet may be out of date. Please download the latest datasheet of LDM182G5005CC001 from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en/products/productdetail?partno=LDM182G5005CC001

## Packaging Information

Packaging	Specifications	Standard Packing Quantity
-	180mm Paper Tape	4000



Chip type SMD baluns constructed with copper conductor and ceramic material. Ideal for high-frequency applications.

- 1. Small, Low-profiled SMD.
- 2. Low loss.
- 3. Available in tape and reel packing for automatic mounting.

#### Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued

without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.





# LDM182G5005CC001

Note: This datasheet may be out of date. Please download the latest datasheet of LDM182G5005CC001 from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en/products/productdetail?partno=LDM182G5005CC001

### Specifications

Center Frequency	2500.00MHz
Frequency Range	2300.00MHz to 2700.00MHz
Insertion Loss I)	0.90dB max. (at 25℃)
Insertion Loss II)	1.00dB max. (-40 to +85°C)
Unbalance Impedance (Nom.)	50Ω
Balance Impedance (Differential) (Nom.)	50Ω
Unbalance Port VSWR	2.00 max. (Balance Port:at 50ohm)
Operating Temperature Range	-40°C to 85°C
L x W (size)	1.60x0.80mm
Thickness(max.)	0.4mm

2 of 2

#### Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued

without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.

