

Product Search Data Sheet

information provided may not be the most current. Please download the latest datasheet of XRCGB48M000F5A00R0 from the official website of Murata

Note: If you have not downloaded this document from our official website, please note that the

XRCGB48M000F5A00R0












Applications

| Unsuitable | Please be sure to read and comply with | |
|--------------------------|--|--|
| Applications | these "Precautions for use." | |
| Specific Applications | Automotive powertrain/safety equipment Please refer to Our Website and specifications, etc. for information about the performance, functions, quality, management, and safety required for | |
| | the above applications, and use Products after confirming the performance and reliability of the actual Product. | |



Appearance & Shape







Packaging Information

| Packaging | Specifications | Standard Packing Quantity |
|-----------|--------------------|---------------------------------|
| R0 | 180mm Plastic Tape | 3000 |



Features

The crystal unit for automotive electronics that realized small package and highly accurate frequency.

Based on Murata's excellent package technology and high grade quartz crystal elements, achieving small size and high accuracy unit.

Features

- 1. The series has high reliability and is available for a wide temperature range.
- 2. The crystal unit is small size (2.0 x 1.6 x 0.7 (mm)), and contribute to reduction in mounting area.
- 3. The series complies to RoHS and ELV directives, being leadfree (phase 3).
- 4. The series complies to AEC-Q200.

1 of 2

- 1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.
- 2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering





Note: If you have not downloaded this document from our official website, please note that the information provided may not be the most current. Please download the latest datasheet of XRCGB48M000F5A00R0 from the official website of Murata

XRCGB48M000F5A00R0



Specifications

| Product Type | Crystal Unit |
|---------------------------------------|--------------------------|
| Series | XRCGB |
| Туре | HCR2016 |
| Frequency | 48.0000MHz |
| Frequency Tolerance | +/-50ppm max. (25+/-3°C) |
| Operating Temperature Range | -40°C~125°C |
| Frequency Shift by Temperature | +/-65ppm max. |
| Frequency Aging | +/-10ppm max./15years |
| Equivalent Series Resistance (ESR) | 60ohm max. |
| Drive Level (DL) | 150μW (300μW max.) |
| Load Capacitance (Cs) | 6pF |
| Shape | SMD |
| Wash | Not available |
| L x W (size) | 2.0x1.6mm |
| Mass | 6.9mg |

2 of 2

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.

