

Product Search Data Sheet

Note: This datasheet may be out of date. Please download the latest datasheet of CFWKA450KGFA-R0 from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en-sg/products/productdetail?partno=CFWKA450KGFA-R0

CFWKA450KGFA-R0









Applications


| Unsuitable | Please be sure to read and comply with | |
|--------------------------|--|--|
| Applications | these "Precautions for use." | |
| Specific Applications | Consumer equipment | |
| | Please refer to Our Website and | |
| | specifications, etc. for information about | |
| | the performance, functions, quality, | |
| | management, and safety required for | |
| | the above applications, and use | |
| | Products after confirming the | |
| | performance and reliability of the actual | |
| | Product. | |



Appearance & Shape













Packaging Information

| Packaging | Specifications | Standard Packing Quantity |
|-----------|---------------------|---------------------------------|
| -R0 | 180mm Embossed Tape | 350 |



Features

The CFWKAseries is comprised of small, high-performance, thin (3.0mm) filters consisting of 6 ceramic elements. The filters are recommend for pager or hand-held cellular phones.

Features

- 1. The filters are mountable by automatic placers.
- 2. The filters can be reflow soldered.
- 3. They are slim, at only 3.0mm maximum thickness.
- 4. The filters are wide bandwidth, flat GDT within pass band.
- 5. Operating temperature range: -20 to +80 (degrees C), Storage temperature range: -40 to +85 (degrees C)

1 of 3

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering





Product Search Data Sheet

Note: This datasheet may be out of date.

Please download the latest datasheet of CFWKA450KGFA-R0 from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en-sg/products/productdetail?partno=CFWKA450KGFA-R0

CFWKA450KGFA-R0



Specifications

| Operating Temperature Range | -20°C to 80°C | |
|-----------------------------|------------------------------|--|
| Shape | SMD | |
| Elements | 6 | |
| Center Frequency | 450.0kHz | |
| Nominal Center Value | Yes | |
| 6dB Bandwidth | fn±4.5kHzmin. | |
| Stop Bandwidth | 11.0kHz | |
| Area of Stop Bandwidth | [within 50dB] | |
| Stop Band Attenuation | 50dB[within fn±100kHz] | |
| Insertion Loss | 6.0dB[at minimum loss point] | |
| Ripple | 2.0dB[within fn±3kHz] | |
| Input/Output Impedance | 1500Ω | |
| Mass | 690mg | |

2 of 3

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.




Note: This datasheet may be out of date. Please download the latest datasheet of CFWKA450KGFA-R0 from the official website of Murata Manufacturing Co., Ltd.


http://www.murata.com/en-sg/products/productdetail?partno=CFWKA450KGFA-R0

CFWKA450KGFA-R0




Product Data





Frequency Characteristics

Spurious Response



Measurement Circuit

3 of 3

- 1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.
- 2. This datasheet has only typical specifications because there is no space for detailed specifications.
- Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.

