

Product Search Data Sheet

Note: This datasheet may be out of date. Please download the latest datasheet of LDM182G4505CC001 from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en-sg/products/productdetail?partno=LDM182G4505CC001

LDM182G4505CC001












Applications

Unsuitable	Please be sure to read and comply with	
Applications	these "Precautions for use."	
Specific Applications	Consumer equipment,Industrial Equipment,Medical equipment [GHTF	
	A/B],Mobile Electronics	
	Please refer to Our Website and	
	specifications, etc. for information about	
	the performance, functions, quality,	
	management, and safety required for	
	the above applications, and use	
	Products after confirming the	
	performance and reliability of the actual	
	Product.	
Recommended Applications	Consumer equipment,Industrial	
	Equipment,Medical equipment [GHTF	
	A/B],Mobile Electronics	



Appearance & Shape





Packaging Information

Packaging		Standard Packing Quantity
-	180mm Paper Tape	4000



Features

Chip type SMD baluns constructed with copper conductor and ceramic material.

Ideal for high-frequency applications.

- 1. Small, Low-profiled SMD.
- 2. Low loss.
- 3. Available in tape and reel packing for automatic mounting.

1 of 2

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.





LDM182G4505CC001

Note: This datasheet may be out of date.

Please download the latest datasheet of LDM182G4505CC001 from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en-sg/products/productdetail?partno=LDM182G4505CC001



Specifications

Center Frequency	2450.00MHz
Frequency Range	2400.00MHz to 2500.00MHz
Insertion Loss I)	0.88dB max. (at 25°C)
Insertion Loss II)	0.98dB max. (-40 to +85°C)
Unbalance Impedance (Nom.)	50Ω
Balance Impedance (Differential) (Nom.)	50Ω
Unbalance Port VSWR	2.00 max. (Balance Port:at 50ohm)
Operating Temperature Range	-40°C to 85°C
L x W (size)	1.60x0.80mm
Thickness(max.)	0.4mm

2 of 2

Attention

1.This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.

