

Product Search Data Sheet

Wound (Ferrite)

Note: If you have not downloaded this document from our official website, please note that the information provided may not be the most current. Please download the latest datasheet of LLM3225-120J from the official website of Murata

LLM3225-120J














Applications

Unsuitable	Please be sure to read and comply with	
Applications	these "Precautions for use."	
	Consumer equipment,Medical	
	equipment [GHTF A/B/C] except for	
	implant & surgery & auto injector,	
	Industrial equipment except for	
	transportation & facility & energy	
	equipment	
Specific	Please refer to Our Website and	
Applications	specifications, etc. for information about	
	the performance, functions, quality,	
	management, and safety required for	
	the above applications, and use	
	Products after confirming the	
	performance and reliability of the actual	
	Product.	
Recommended	Consumer equipment	
Applications		



Appearance & Shape







Notices

Rated current is specified when the decrease of the initial inductance value at 10%. Or rated current is specified when temperature of the inductor is raised 20°C by DC current. Whichever is smaller.



References

Packaging	Specifications	Standard Packing Quantity
-	180Embossed Tape	2000

Mass (typ.)		
1 piece	0.04g	

1 of 3

- 1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.
- 2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.





LLM3225-120J

Note: If you have not downloaded this document from our official website, please note that the information provided may not be the most current.

Please download the latest datasheet of LLM3225-120J from the official website of Murata

http://www.murata.com/en-sg/products/productdetail?partno=LLM3225-120



Specifications

L size	3.2±0.2mm
W size	2.5±0.2mm
T size	2.4mm
Size code inch (mm)	1210 (3225)
Inductance	12μH±5%
Inductance Test Frequency	2.52MHz
Max. of DC resistance	1.9Ω
Operating Temperature Range (Self-temperature	-40°C to 85°C
rise is included)	
Class of magnetic shield	Non-Shielded
Q(min.)	30
Q Test Frequency	2.52MHz
Self resonance frequency (min.)	23MHz
Brand	Murata
Rated Current	200mA
Series	LLM3225

2 of 3

Attention

1.This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.



LLM3225-120J


Note: If you have not downloaded this document from our official website, please note that the information provided may not be the most current.

Please download the latest datasheet of LLM3225-120J from the official website of Murata

http://www.murata.com/en-sg/products/productdetail?partno=LLM3225-120



Characteristic Data



Q-Frequency Characteristics

3 of 3

Attention

1.This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.

