

DLM0NSM900HY2#

Note: This datasheet may be out of date

Please download the latest datasheet of DLM0NSM900HY2# from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en-sg/products/productdetail?partno=DLM0NSM900HY2%23

"#"at the end indicates the package specification code.







< List of part numbers with package codes > DLM0NSM900HY2B DLM0NSM900HY2D



Applications


Unsuitable	Please be sure to read and comply with	
Applications	these "Precautions for use."	
	Consumer Electronics - Differential	
	Transmission,Medical equipment [GHTF	
	A/B/C] except for implant & surgery &	
	auto injector,Industrial equipment	
	except for transportation & facility &	
	energy equipment	
Specific Applications	Please refer to Our Website and	
	specifications, etc. for information about	
	the performance, functions, quality,	
	management, and safety required for	
	the above applications, and use	
	Products after confirming the	
	performance and reliability of the actual	
	Product.	
Recommended	Consumer equipment,USB2.0,USB3.1	
	Gen1,USB3.1 Gen2,MIPI D-PHY Ver1.1,	
Applications	MIPI D-PHY Ver1.2,HDMI 1.4b	



Appearance & Shape









Packaging Information

	Specifications	Standard
Packaging		Packing
		Quantity
В	Bulk(Bag)	500
D	180mm Paper Tape	10000



Features

- 1. Small size and tight dimensional tolerance Size:0.85x0.65x0.45mm Tolerance:+-0.05mm
- 2. High common mode impedance up to 90ohm (at 100MHz) is available.
- DLM0NSM series enables noise suppression for differential signal line without distortion in highspeed signal transmission due to its line impedance matching.
- 4. High Cut-off Frequency.

1 of 3

Attention

- 1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.
- 2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.





DLM0NSM900HY2#

Note: This datasheet may be out of date.

Please download the latest datasheet of DLM0NSM900HY2# from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en-sg/products/productdetail?partno=DLM0NSM900HY2%23

"#"at the end indicates the package specification code.



Specifications

Shape	SMD
	1
Size Code (in mm)	0806
Size Code (in inch)	03025
Length	0.85mm
Length Tolerance	±0.05mm
Width	0.65mm
Width Tolerance	±0.05mm
Thickness	0.45mm
Thickness Tolerance	±0.05mm
Common Mode Impedance (at 100MHz)	90Ω
Common Mode Impedance (at 100MHz) Tolerance	±25%
Rated Current	100mA
Derating of Rated Current	No
Rated Voltage	5Vdc
Withstanding Voltage	12.5Vdc
DC Resistance(max.)	4.75Ω
DC Resistance	3.8Ω±25%
Insulation Resistance(min.)	10ΜΩ
Cut-off Frequency	5.0GHz (Typ.)
Operating Temperature Range	-40°C to 85°C
Mass(typ.)	0.9mg
Number of Circuit	1
Operating Temperature Range(Self-temperature rise is included)	No

Brand	Murata

2 of 3

- 1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.
- 2. This datasheet has only typical specifications because there is no space for detailed specifications.
- Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.



DLM0NSM900HY2#


Note: This datasheet may be out of date.


Please download the latest datasheet of DLM0NSM900HY2# from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en-sg/products/productdetail?partno=DLM0NSM900HY2%23


"#"at the end indicates the package specification code.

Product Data






Impedance-Frequency Characteristics



Note1: The Port/Pin No. of the Simulation Model provided by our company is



Equivalent Circuit

Differential Mode Transmission Characteristics (Typical Value)

3 of 3

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering

