

Product Search Data Sheet

Note: This datasheet may be out of date.

Please download the latest datasheet of MYBSS054R6EBF from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en-sg/products/productdetail?partno=MYBSS054R6EBF

mybss054r6ebf









Applications

Unsuitable	Please be sure to read and comply with	
Applications	these "Precautions for use."	
	Consumer equipment,Industrial	
	Equipment	
	Please refer to Our Website and	
	specifications, etc. for information about	
Specific	the performance, functions, quality,	
Applications	management, and safety required for	
	the above applications, and use	
	Products after confirming the	
	performance and reliability of the actual	
	Product.	
Recommended	DoE [Dower over Ethernet]	
Applications	PoE [Power over Ethernet]	



Features

30W, 54V/0.6Aboost-up isolated DC-DC converter for PSE of PoE Input voltage ranges from 10.8 to 27V Small package, 35.5 x 22.4 x 8.9mm Surface mount module 2250Vdc Input-Output Isolation



Appearance & Shape



1 of 2

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.





Note: This datasheet may be out of date. Please download the latest datasheet of MYBSS054R6EBF from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en-sg/products/productdetail?partno=MYBSS054R6EBF

Specifications

mybss054r6ebf

Output power (W)Max	30W
Vin(V)	10.8V to 27V
Vin(V)typ	24V
Vout(V)	54V
Vout(V)typ	54V
Isolation Voltage (V)	2250V
Efficiency (%)	90.5%
Size(mm)W	35.5mm
Size(mm)L	22.4mm
Size(mm)T	8.9mm
Operatingtemperature(degC)	-40°C to 85°C
Outputs (#)	1
lout(A)Max	0.6A
Package	SMD
Productseries	МУВ
Product Series Features	MYBSS series is boost-up isolated DC-DC converter for PoE especially PSE.
Brand	Murata

2 of 2

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.

