Note: If you have not downloaded this document from our official website, please note that the information provided may not be the most current.

Please download the latest datasheet of MYC0409-NA from the official website of Murata

http://www.murata.com/en-sg/products/productdetail?partno=MYC0409-NA

## MYC0409-NA

20V to 60V input voltage, 6A, 72W Charge pump with 120degC Tj









### **Applications**

Unsuitable	Please be sure to read and comply with
Applications	these "Precautions for use."
	Consumer equipment,Industrial
	Equipment
	Please refer to Our Website and
	specifications, etc. for information about
Specific	the performance, functions, quality,
Applications	management, and safety required for
	the above applications, and use
	Products after confirming the
	performance and reliability of the actual
	Product.
	Processor [ASIC / FPGA / xPU],Optical
Recommended	Backbone network,Optical Module,
Applications	Server,Storage,Switch,Base Station,
	Industrial Equipment





### Features

Enable, Power Good, Frequency Synchronization, Over Current Protection, Over Temperature Protection, UVLO, Parallel Operation



### Appearance & Shape





1 of 2

### Attentior

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

 $2. This \ data{sheet has only typical specifications because there is no \ space for \ detailed \ specifications.}$ 

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.





### Product Search Data Sheet

information provided may not be the most current. Please download the latest datasheet of MYC0409-NA from the official website of Murata

Note: If you have not downloaded this document from our official website, please note that the

# MYC0409-NA



# Specifications

lout(A)Max	6A
Vin(V)	20V to 60V
Vin(V)typ	48V
Vout(V)	5V to 15V
Vout(V)typ	12V
Outputs (#)	1
Efficiency (%)	96.5%
Size(mm)W	11.5mm
Size(mm)L	9.5mm
Size(mm)T	2.0mm
Operatingtemperature(degC)	-40°C to 105°C
Circuit topology	Charge pump
Package	SMD
Туре	Modules (integrated components)
Product Series Features	Ultra-Thin, Fully Integrated Charge pump, Capacitor divider module
Brand	Murata

2 of 2

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.

