

Product Search Data Sheet

Note: If you have not downloaded this document from our official website, please note that the information provided may not be the most current. Please download the latest datasheet of RHS7J2D471J1A2H01B from the official website of Murata

# RHS7J2D471J1A2H01B

























## **Applications**

Unsuitable	Please be sure to read and comply with
	1 7
Applications	these "Precautions for use."
	Automotive powertrain/safety equipment,
	Automotive infotainment/comfort
	equipment,Medical equipment [GHTF
	A/B/C] except for implant equipment
	Please refer to Our Website and
Specific	specifications, etc. for information about
Applications	the performance, functions, quality,
	management, and safety required for
	the above applications, and use
	Products after confirming the
	performance and reliability of the actual
	Product.



#### **Notices**

HF(Halogen Free), Derating5




### References

	Specifications	Standard
Packaging		Packing
		Quantity
В	Bulk(Bag)	500

Mass (typ.)	
1 piece	0.11g

## Appearance & Shape





1 of 3

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.





Note: If you have not downloaded this document from our official website, please note that the information provided may not be the most current.

Please download the latest datasheet of RHS7J2D471J1A2H01B from the official website of Murata

http://www.murata.com/en-sq/products/productdetail?partno=RHS7J2D471J1A2H01

# RHS7J2D471J1A2H01B



# **Specifications**

L size or Outer diameter D	4.2mm max.
Width	3.5mm max.
T size	2.8mm max.
Lead spacing F	2.5±0.8mm
Lead diameter d	0.5±0.05mm
Paint dripping e	2.0mm max.
Capacitance	470pF ±5%
Rated voltage	200Vdc
Temperature characteristics	UNJ(MURATA)
Temperature range of temperature characteristics	-55°C to 200°C
Operating Temperature Range	-55°C to 200°C
тс	-55°C to 25°C: -750+120/- 347ppm/°C 25°C to 125°C: - 750±120ppm/°C 125°C to 200°C: -750+347/-120ppm/°C

2 of 3

#### Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.



#### Product Search Data Sheet


information provided may not be the most current. Please download the latest datasheet of RHS7J2D471J1A2H01B from the official website of Murata


Note: If you have not downloaded this document from our official website, please note that the

# RHS7J2D471J1A2H01B



### Characteristic Data





Capacitance - temperature characteristics

Impedance - frequency characteristics

3 of 3

#### Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.

