

## GJM0335C1E5R6BB01D

Note: If you have not downloaded this document from our official website, please note that the information provided may not be the most current.

Please download the latest datasheet of GJM0335C1E5R6BB01# from the official website of Murata

http://www.murata.com/en-sg/products/productdetail?partno=GJM0335C1E5R6BB01%23

"#"at the end indicates the package specification code.











< List of part numbers with package codes > GJM0335C1E5R6BB01D GJM0335C1E5R6BB01W GJM0335C1E5R6BB01V

GJM0335C1E5R6BB01J



### **Applications**

Unsuitable	Please be sure to read and comply with
Applications	these "Precautions for use."
	' '
	Products after confirming the
	performance and reliability of the actual
	Product.



### References


Packaging	Specifications	Standard Packing Quantity
D	φ180mm Reel Paper Tape	15000
W	φ180mm Reel W8P1 Paper Tape	30000
J	φ330mm Reel Paper Tape	50000
V	φ330mm Reel W8P1 Paper Tape	150000

Mass (typ.)	
1 piece	0.33mg



### Appearance & Shape





1 of 2

#### Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

 $2. This \ data{sheet has only typical specifications because there is no \ space for \ detailed \ specifications.}$ 

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.





# GJM0335C1E5R6BB01D

Note: If you have not downloaded this document from our official website, please note that the information provided may not be the most current.

Please download the latest datasheet of GJM0335C1E5R6BB01# from the official website of Murata

http://www.murata.com/en-sg/products/productdetail?partno=GJM0335C1E5R6BB01%23

"#"at the end indicates the package specification code.



## **Specifications**

Length	0.6±0.03mm
Width	0.3±0.03mm
Thickness	0.3±0.03mm
Capacitance	5.6pF ±0.1pF
Distance between external terminals g	0.2mm min.
External terminal size e	0.1 to 0.2mm
Operating Temperature Range	-55°C to 125°C
Rated Voltage	25Vdc
Size code in inch(mm)	0201 (0603M)
тс	0±30ppm/°C
Temperature characteristics (complied standard)	C0G(EIA)
Temperature range of temperature characteristics	25°C to 125°C

2 of 2

#### Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.

