



Note: If you have not downloaded this document from our official website, please note that the information provided may not be the most current.

Please download the latest datasheet of CSTCG33M0V53-R0 from the official website of Murata

CSTCG33M0V53-R0










Applications

Unsuitable	Please be sure to read and comply with	
Applications	these "Precautions for use."	
Specific Applications	Consumer equipment	
	Please refer to Our Website and	
	specifications, etc. for information about	
	the performance, functions, quality,	
	management, and safety required for	
	the above applications, and use	
	Products after confirming the	
	performance and reliability of the actual	
	Product.	



Appearance & Shape







Packaging Information

Packaging	Specifications	Standard Packing Quantity
R0 180mm Embossed Tape 3000		3000



Features

MURATA's package technology expertise has enabled the development of the Chip CERALOCK. High-density mounting can be realized because of the small package and the elimination of the need for an external load capacitor.

Features

- 1. Oscillation circuits do not require external load capacitors.
- 2. Available in a wide frequency range.
- 3. Extremely small and have a low profile.
- 4. No adjustment is necessary for oscillation circuits.

1 of 2

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering





Note: If you have not downloaded this document from our official website, please note that the h Data Sheet information provided may not be the most current.

Please download the latest datasheet of CSTCG33M0V53-R0 from the official website of Murata

http://www.murata.com/en-sg/products/productdetail?partno=CSTCG33M0V53-R

CSTCG33M0V53-R0



Specifications

	Ceramic Resonator	
Product Type		
	(CERALOCK)	
Series	CSTCG_V	
Frequency	33.000MHz	
Frequency Tolerance	+/-0.50% max.	
Operating Temperature	00% 00%	
Range	-20°C~80°C	
Frequency Shift by	. / 0 000/	
Temperature	+/-0.30% max.	
Frequency Aging	+/-0.20% max.	
Trequency Aging	17-0.20 % Max.	
Resonant Impedance (R1)	50ohm max.	
Built-in Load Capacitance		
'	15pF	
(CL1/CL2)		
Shape	SMD	
Mark	Not eveileble	
Wash	Not available	
L x W (size)	2.0x1.3mm	
27.17 (0.20)		
Mass	13mg	

2 of 2

Attention

1.This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.

