

Product Search Data Sheet

Note: If you have not downloaded this document from our official website, please note that the information provided may not be the most current. Please download the latest datasheet of CSTCW24M0X51R-R0 from the official website of Murata

CSTCW24M0X51R-R0










Applications

| Unsuitable | Please be sure to read and comply with |
|--------------|--|
| Applications | these "Precautions for use." |
| | Consumer equipment |
| | Please refer to Our Website and |
| | specifications, etc. for information about |
| CiG- | the performance, functions, quality, |
| Specific | management, and safety required for |
| Applications | the above applications, and use |
| | Products after confirming the |
| | performance and reliability of the actual |
| | Product. |



Appearance & Shape







Packaging Information

| Packaging | Specifications | Standard Packing Quantity |
|-----------|---------------------|---------------------------------|
| R0 | 180mm Embossed Tape | 3000 |



Features

MURATA's package technology expertise has enabled the development of the Chip CERALOCK. High-density mounting can be realized because of the small package and the elimination of the need for an external load capacitor.

Features

- 1. Oscillation circuits do not require external load capacitors.
- 2. Available in a wide frequency range.
- 3. Extremely small and have a low profile.
- 4. No adjustment is necessary for oscillation circuits.

1 of 2

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.





Note: If you have not downloaded this document from our official website, please note that the information provided may not be the most current.

Please download the latest datasheet of CSTCW24M0X51R-R0 from the official website of Murata

http://www.murata.com/en-sg/products/productdetail?partno=CSTCW24M0X51R-R

CSTCW24M0X51R-R0



Specifications

| Dec duct Tues | Ceramic Resonator |
|---------------------------|-------------------|
| Product Type | (CERALOCK) |
| Series | CSTCW_X_R |
| Frequency | 24.000MHz |
| Frequency Tolerance | +/-0.50% max. |
| Operating Temperature | 00% 00% |
| Range | -20°C~80°C |
| Frequency Shift by | . / 0 000/ |
| Temperature | +/-0.20% max. |
| Frequency Aging | +/-0.10% max. |
| Resonant Impedance (R1) | 80ohm max. |
| Built-in Load Capacitance | 0.5 |
| (CL1/CL2) | 6pF |
| Shape | SMD |
| Wash | Not available |
| L x W (size) | 2.5x2.0mm |
| Mass | 32mg |

2 of 2

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.

