

Product Search Data Sheet

Note: This datasheet may be out of date.

Please download the latest datasheet of CSALS33M8X51-A0 from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en-us/products/productdetail?partno=CSALS33M8X51-A0

CSALS33M8X51-A0










Applications

Unsuitable	Please be sure to read and comply with	
Applications	these "Precautions for use."	
Specific Applications	Consumer equipment	
	Please refer to Our Website and	
	specifications, etc. for information about	
	the performance, functions, quality,	
	management, and safety required for	
	the above applications, and use	
	Products after confirming the	
	performance and reliability of the actual	
	Product.	



Appearance & Shape







Packaging Information

Packaging	Specifications	Standard Packing Quantity
A0	Ammo Pack	2000



Features

MURATA's ceramic resonator, CERALOCK has been widely applied as the most suitable component for clock oscillators in a broad range of microprocessors.

Features

- 1. Stable over a wide temperature range.
- 2. Compact, lightweight and exhibit superior shock resistance performance.
- 3. Cost-effective and reliable availability.

1 of 2

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.





Product Search Data Sheet

Note: This datasheet may be out of date. Please download the latest datasheet of CSALS33M8X51-A0 from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en-us/products/productdetail?partno=CSALS33M8X51-A0

CSALS33M8X51-A0



Specifications

	Ceramic Resonator	
Product Type		
	(CERALOCK)	
Series	CSALS_X	
Frequency	33.868MHz	
Frequency Tolerance	+/-0.50% max.	
Operating Temperature	00%5 00%5	
Range	-20°C~80°C	
Frequency Shift by		
Temperature	+/-0.20% max.	
Frequency Aging	+/-0.20% max.	
Resonant Impedance (R1)	40ohm max.	
Shape	Lead	
Wash	Not available	
VVGGII	TVOL A VAIIADIO	
L x W (size)	6.5x7.0mm	
Mass	137mg	

2 of 2

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.

