Note: This datasheet may be out of date. Please download the latest datasheet of NTPA94R0LBMB0 from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en-us/products/productdetail?partno=NTPA94R0LBMB0

# NTPA94R0LBMB0










## **Applications**

Unsuitable	Please be sure to read and comply with	
Applications	these "Precautions for use."	
	Industrial Equipment	
	Please refer to Our Website and	
	specifications, etc. for information about	
Specific	the performance, functions, quality,	
'	management, and safety required for	
Applications	the above applications, and use	
	Products after confirming the	
	performance and reliability of the actual	
	Product.	



## Appearance & Shape





### Packaging Information

Packaging	Specifications	Standard Packing Quantity
В0	Bulk(Bag)	300



#### **Features**

- 1. Lead is not contained in the ceramic element, the terminations, the solder for inner connection and the coating resin.
- 2. Most suitable for power supplies of less than 100W
- 3. Excellent recovery characteristics due to resin coating with excellent heat characteristics

1 of 3

- 1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.
- 2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.





# NTPA94R0LBMB0

Note: This datasheet may be out of date.

Please download the latest datasheet of NTPA94R0LBMB0 from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en-us/products/productdetail?partno=NTPA94R0LBMB0



# **Specifications**

Resistance (25°C)	4Ω	
Resistance Value Tolerance	.450/	
(at 25°C)	±15%	
Permissible Max. Current	0.54	
(25°C)	2.5A	
Permissible Max. Current	0.04	
(55°C)	2.2A	
Thermal Time Constant	65s	
Typical Dissipation Constant	4.4 Cma\N/9C	
(25°C)	11.6mW/°C	
Permissible Electrolytic	800µF	
Capacitor	ουυμε	
Measure Condition of		
Permissible Electrolytic	at 100V	
Capacitor		
Operating Temperature	-20°C to 160°C	
Range	-20 C to 160 C	
Lead Shape	Lead Wire type	
Shape	Lead	
Mass	0.79g	
MSL	N	

2 of 3

#### Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.



#### Product Search Data Sheet


Note: This datasheet may be out of date. Please download the latest datasheet of NTPA94R0LBMB0 from the official website of Murata Manufacturing Co., Ltd.


http://www.murata.com/en-us/products/productdetail?partno=NTPA94R0LBMB0

# NTPA94R0LBMB0




### **Product Data**





#### Permissible Maximum Current Derating Curve



### Current-R ratio(Rt/R25), Current-Temperature Characteristics

Permissible Electrolytic Capacitor

3 of 3

- 1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.
- 2. This datasheet has only typical specifications because there is no space for detailed specifications.
- Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.

